



Department of Agriculture
BUREAU OF SOILS AND WATER MANAGEMENT
"NATIONAL SOIL SAMPLING AND TESTING FOR FERTILITY AND CROP SUITABILITY ASSESSMENT"
FERTILIZER-GUIDE FOR RICE
PROVINCE OF ILOCOS SUR

Municipality	Fertilizer-Guide Group		Additional 10-20 bags/ha Organic Fertilizer is recommended for all options															
			INBRED RICE									HYBRID RICE						
			WET SEASON				DRY SEASON					WET SEASON				DRY SEASON		
	Number	Description	Nutrient Requirement			Recommended Fertilizer Rate (bags/hectare)	Nutrient Requirement			Recommended Fertilizer Rate (bags/hectare)	Nutrient Requirement			Recommended Fertilizer Rate (bags/hectare)	Nutrient Requirement			Recommended Fertilizer Rate (bags/hectare)
N			P ₂ O ₅	K ₂ O	N		P ₂ O ₅	K ₂ O	N		P ₂ O ₅	K ₂ O	N		P ₂ O ₅	K ₂ O		
SANTA CATALINA	080	M-L-H-H	90	7	7	Option 1: (1st Application): 1.00 (14-14-14-); 1.75 (46-0-0); (2nd Application): 1.00 (46-0-0); (3rd Application): 1.00 (46-0-0); Option 2: (1st Application): 0.75 (16-20-0); (2nd Application): 2.00 (46-0-0); (3rd Application): 1.75 (46-0-0); 0.25 (0-0-60); Option 3: (1st Application): 2.00 (46-0-0); 1.00 (0-18-0); (2nd Application): 1.00 (46-0-0); (3rd Application): 1.00 (46-0-0); 0.25 (0-0-60);	100	7	7	Option 1: (1st Application): 1.00 (14-14-14-); 2.00 (46-0-0); (2nd Application): 1.25 (46-0-0); (3rd Application): 1.25 (46-0-0); Option 2: (1st Application): 0.75 (16-20-0); (2nd Application): 2.25 (46-0-0); (3rd Application): 2.00 (46-0-0); 0.25 (0-0-60); Option 3: (1st Application): 2.25 (46-0-0); 1.00 (0-18-0); (2nd Application): 1.25 (46-0-0); (3rd Application): 1.25 (46-0-0); 0.25 (0-0-60);	110	7	7	Option 1: (1st Application): 1.00 (14-14-14-); 2.25 (46-0-0); (2nd Application): 1.25 (46-0-0); (3rd Application): 1.25 (46-0-0); Option 2: (1st Application): 0.75 (16-20-0); (2nd Application): 4.75 (46-0-0); (3rd Application): 0.25 (0-0-60); Option 3: (1st Application): 2.50 (46-0-0); 1.00 (0-18-0); (2nd Application): 1.25 (46-0-0); (3rd Application): 1.25 (46-0-0); 0.25 (0-0-60);	120	7	7	Option 1: (1st Application): 1.00 (14-14-14-); 2.50 (46-0-0); (2nd Application): 1.50 (46-0-0); (3rd Application): 1.50 (46-0-0); Option 2: (1st Application): 0.75 (16-20-0); (2nd Application): 3.00 (46-0-0); (3rd Application): 2.00 (46-0-0); 0.25 (0-0-60); Option 3: (1st Application): 2.75 (46-0-0); 1.00 (0-18-0); (2nd Application): 1.50 (46-0-0); (3rd Application): 1.50 (46-0-0); 0.25 (0-0-60);
SANTA CATALINA	071	M-L-ML-MH	90	40	20	Option 1: (1st Application): 3.00 (14-14-14-); 1.25 (46-0-0); 2.25 (0-18-0); (2nd Application): 1.00 (46-0-0); (3rd Application): 1.00 (46-0-0); Option 2: (1st Application): 4.00 (16-20-0); (2nd Application): 1.50 (46-0-0); (3rd Application): 1.00 (46-0-0); 0.75 (0-0-60); Option 3: (1st Application): 2.00 (46-0-0); 4.50 (0-18-0); (2nd Application): 1.00 (46-0-0); (3rd Application): 1.00 (46-0-0); 0.75 (0-0-60);	100	40	20	Option 1: (1st Application): 3.00 (14-14-14-); 1.30 (46-0-0); 2.22 (0-18-0); (2nd Application): 1.09 (46-0-0); (3rd Application): 1.09 (46-0-0); Option 2: (1st Application): 4.00 (16-20-0); (2nd Application): 2.00 (46-0-0); (3rd Application): 1.00 (46-0-0); 0.75 (0-0-60); Option 3: (1st Application): 2.25 (46-0-0); 4.50 (0-18-0); (2nd Application): 1.25 (46-0-0); (3rd Application): 1.25 (46-0-0); 0.75 (0-0-60);	110	50	30	Option 1: (1st Application): 4.50 (14-14-14-); 1.25 (46-0-0); 2.22 (0-18-0); (2nd Application): 1.20 (46-0-0); (3rd Application): 1.20 (46-0-0); Option 2: (1st Application): 5.00 (16-20-0); (2nd Application): 2.00 (46-0-0); (3rd Application): 1.25 (46-0-0); 1.00 (0-0-60); Option 3: (1st Application): 2.50 (46-0-0); 5.75 (0-18-0); (2nd Application): 1.25 (46-0-0); (3rd Application): 1.25 (46-0-0); 1.00 (0-0-60);	120	50	30	Option 1: (1st Application): 4.50 (14-14-14-); 1.50 (46-0-0); 2.25 (0-18-0); (2nd Application): 1.50 (46-0-0); (3rd Application): 1.50 (46-0-0); Option 2: (1st Application): 5.00 (16-20-0); (2nd Application): 2.00 (46-0-0); (3rd Application): 1.50 (46-0-0); 1.00 (0-0-60); Option 3: (1st Application): 2.75 (46-0-0); 5.25 (0-18-0); (2nd Application): 1.50 (46-0-0); (3rd Application): 1.50 (46-0-0); 1.00 (0-0-60);