

## **Bureau of Soils and Water Management PHILIPPINE BIDDING DOCUMENTS** (As Harmonized with Development Partners)

# Procurement of 1 unit of Mobile Soil Laboratory (under GAA 2023) for CY 2024

## **IB NO: BSWM-2024-02-0027**

Date issued February 2024

## **PHILIPPINE BIDDING DOCUMENTS**

# Procurement of GOODS

Government of the Republic of the Philippines

Sixth Edition July 2020

### Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

- a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the particular Procurement Project.
- b. Specific details, such as the "*name of the Procuring Entity*" and "*address for bid submission*," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.

- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.
- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of Foreign-Assisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

## **Table of Contents**

Gloss	ary of Acronyms, Terms, and Abbreviations	5
Sectio	on I. Invitation to Bid	8
Sectio	on II. Instructions to Bidders	12
1.	Scope of Bid	13
2.	Funding Information	13
3.	Bidding Requirements	13
4.	Corrupt, Fraudulent, Collusive, and Coercive Practices	13
5.	Eligible Bidders	13
6.	Origin of Goods	14
7.	Subcontracts	14
8.	Pre-Bid Conference	15
9.	Clarification and Amendment of Bidding Documents	15
10.	Documents comprising the Bid: Eligibility and Technical Components	15
11.	Documents comprising the Bid: Financial Component	16
12.	Bid Prices	16
13.	Bid and Payment Currencies	17
14.	Bid Security	17
15.	Sealing and Marking of Bids	17
16.	Deadline for Submission of Bids	17
17.	Opening and Preliminary Examination of Bids	17
18.	Domestic Preference	18
19.	Detailed Evaluation and Comparison of Bids	18
20.	Post-Qualification	19
21.	Signing of the Contract	19
Sectio	on III. Bid Data Sheet	20
Sectio	on IV. General Conditions of Contract	22
1.	Scope of Contract	23
2.	Advance Payment and Terms of Payment	23
3.	Performance Security	23
4.	Inspection and Tests	23
5.	Warranty	24
6.	Liability of the Supplier	24
Sectio	on V. Special Conditions of Contract	25
Sectio	on VI. Schedule of Requirements	30
Sectio	on VII. Technical Specifications	32
Sectio	on VIII. Checklist of Technical and Financial Documents	37

## Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*.(2016 revised IRR, Section 5[c])

**Bidder** – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

**Bidding Documents** – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

**BIR** – Bureau of Internal Revenue.

BSP – BangkoSentral ng Pilipinas.

**Consulting Services** – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to:

(i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

**Contract** – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

**CIF** – Cost Insurance and

Freight. CIP - Carriage and Insurance

Paid. CPI – Consumer Price Index.

DDP - Refers to the quoted price of the Goods, which means "delivered duty paid."

**DTI** – Department of Trade and Industry.

EXW – Ex works.

FCA – "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

**Foreign-funded Procurement or Foreign-Assisted Project**–Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

**Framework Agreement** – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC -Government-owned and/or -controlled corporation.

**Goods** – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB –Government Procurement Policy Board.

**INCOTERMS** – International Commercial Terms.

**Infrastructure Projects** – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national

buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC – Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

**Procurement Project** – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

**PSA** – Philippine Statistics Authority.

**SEC** – Securities and Exchange Commission.

**SLCC** – Single Largest Completed Contract.

**Supplier** – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

**UN** – United Nations.

#### Notes on the Invitation to Bid

The Invitation to Bid (IB) provides information that enables potential Bidders to decide whether to participate in the procurement at hand. The IB shall be posted in accordance with Section 21.2 of the 2016 revised IRR of RA No. 9184.

Apart from the essential items listed in the Bidding Documents, the IB should also indicate the following:

- a. The date of availability of the Bidding Documents, which shall be from the time the IB is first advertised/posted until the deadline for the submission and receipt of bids;
- b. The place where the Bidding Documents may be acquired or the website where it may be downloaded;
- c. The deadline for the submission and receipt of bids; and
- d. Any important bid evaluation criteria (*e.g.*, the application of a margin of preference in bid evaluation).

The IB should be incorporated in the Bidding Documents. The information contained in the IBmust conform to the Bidding Documents and in particular to the relevant information in the Bid Data Sheet.



Republic of the Philippines Department of Agriculture **BUREAU OF SOILS AND WATER MANAGEMENT** SRDC Bldg., Elliptical Road corner Visayas Avenue, Diliman, Quezon City 1101

#### **INVITATION TO BID**

## Procurement of 1 unit of Mobile Soil Laboratory (under GAA 2023) for CY 2024- IB NO: BSWM-2024-02-0027

- The Bureau of Soils and Water Management (BSWM), through the General Appropriation Act for CY 2023 intends to apply the sum of Procurement of 1 unit of Mobile Soil Laboratory for CY 2024- IB NO: BSWM-2024-02-0027 in the amount of Forty-Three Million Pesos (PhP 43,000,000.00). Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The BSWM now invites bids for the above Procurement Project. Delivery of the Goods is required within 150 Calendar days upon receipt of Notice to Proceed. Bidders should have completed, within five (5) years from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- 3. Bidding will be conducted through open competitive bidding procedures using a non-discretionary "pass/fail" criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.

Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA 5183.

- Prospective Bidders may obtain further information from BSWM Bids and Awards Committee (BAC) Secretariat's Office and inspect the Bidding Documents at the given address during MONDAY TO FRIDAY, 8:00AM TO 5:00 PM EXCEPT ON DECLARED HOLIDAYS OR WORK SUSPENSION.
- 5. A complete set of Bidding Documents may be acquired by interested Bidders until **March 20, 2024**, **3:00PM** from the given address and website and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of **PhP 25,000.00**. The Procuring Entity shall allow the bidder to present its proof of payment for the fees to BAC Secretariat on or before the deadline of Submission and Opening of Bids.
- 6. The BSWM will hold a **Pre-Bid Conference** on <u>March 7, 2024, 9:30AM at BSWM Convention Hall and</u> shall be open to prospective bidders. Pre-Bid Conference will be available "live" thru **BSWM Procurement Service Facebook Page (FB) Page (https://www.facebook.com/bswmpms).** Furthermore, all interested bidders can participate through videoconferencing. Please coordinate with BAC Secretariat at least a day before the meeting at <u>bac@bswm.da.gov.ph</u>.
- 7. **Bids must be duly received** by the BAC Secretariat through manual submission at the office address indicated below on or before **March 21, 2024, 2023, 9:00AM**. Late bids shall not be accepted.

All Bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in ITB Clause 16.

8. **Bid opening shall be on March 21, 2024, 9:30AM** at the **BSWM Convention Hall**, 2nd Floor, SRDC Bldg., Visayas Ave. Cor. Elliptical Road, Diliman, Quezon City and through videoconferencing/webcasting via ZOOM and streamed live through BSWM Procurement Service FB Page. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.

During the opening of bids, bidder's representative must present his/her company identification card and authorization letter from the head of the company.

- 10. BSWM adheres to the Data Privacy Act under RA 10173.
- 11. The BSWM reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 12. For further information, please refer to: FRANCE JOSEPHINE C. BAUTISTA BIDS AND AWARDS COMMITTEE SECRETARIAT'S OFFICE 2ND FLOOR, SRDC BLDG., VISAYAS AVE. COR. ELLIPTICAL ROAD, DILIMAN, QUEZON CITY TELEFAX NUMBER: +63-2-8273-2474 loc 3218 EMAIL ADDRESS: <u>bac@bswm.da.gov.ph</u> or <u>bswm.bacsec@gmail.com</u> WEBSITE: <u>www.bswm.gov.ph</u> FB Page: <u>https://www.facebook.com/bswmpms</u>

You may visit the following websites: For downloading of Bidding Documents: PhilGEPS- https://notices.philgeps.gov.ph/, BSWM Website- www.bswm.gov.ph or BSWM Procurement Service Facebook Page- <u>https://www.facebook.com/bswmpms</u>.

> (Sgd)DENISE A. SOLANO BSWM BAC Chairperson

## Section II. Instructions to Bidders

#### Notes on the Instructions to Bidders

This Section on the Instruction to Bidders (ITB) provides the information necessary for bidders to prepare responsive bids, in accordance with the requirements of the Procuring Entity. It also provides information on bid submission, eligibility check, opening and evaluation of bids, post-qualification, and on the award of contract.

#### 1. Scope of Bid

The Procuring Entity, *Bureau of Soils and Water Management* wishes to receive Bids for the **Procurement of 1 unit of Mobile Soil Laboratory (under GAA 2023) for CY 2024- IB NO: BSWM-2024-02-0027.** 

The Procurement Project (referred to herein as "Project") is composed of **1 Lot**, the details of which are described in Section VII (Technical Specifications).

#### 2. Funding Information

- 2.1. The GOP through the source of funding as indicated below for 2023 in the amount of **Forty-Three Million Pesos (PhP 43,000,000.00)**
- 2.2. The source of funding is: (GAA 2023)

[If an early procurement activity, select one and delete others:]

a. NGA, the National Expenditure Program.

b. GOCC and GFIs, the proposed Corporate Operating Budget.

c. LGUs, the proposed Local Expenditure Program.

[If not an early procurement activity, select one and delete others:]

- a. NGA, the General Appropriations Act or Special Appropriations.
- b. GOCC and GFIs, the Corporate Operating Budget.
- c. LGUs, the Annual or Supplemental Budget, as approved by the Sanggunian.

#### 3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the

general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

#### 4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

#### 5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. [Select one, delete other/s]

a. Foreign ownership exceeding those allowed under the rules may participate pursuant to:

- i. When a Treaty or International or Executive Agreement as provided in Section 4 of the RA No. 9184 and its 2016 revised IRR allow foreign bidders to participate;
- ii. Citizens, corporations, or associations of a country, included in the list issued by the GPPB, the laws or regulations of which grant reciprocal rights or privileges to citizens, corporations, or associations of the Philippines;
- iii. When the Goods sought to be procured are not available from local suppliers; or
- iv. When there is a need to prevent situations that defeat competition or restrain trade.
- b. Foreign ownership limited to those allowed under the rules may participate in this Project.
- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:
  - **a.** For the procurement of Non-expendable Supplies and Services: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC.
  - b. For the procurement of Expendable Supplies: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least twenty-five percent (25%) of the ABC.
  - c. For procurement where the Procuring Entity has determined, after the conduct of market research, that imposition of either (a) or (b) will likely result to failure of bidding or monopoly that will defeat the purpose of public bidding: the Bidder should comply with the following requirements:
    - i. Completed at least two (2) similar contracts, the aggregate amount of which should be equivalent to at least *fifty percent (50%)* of the ABC per for this Project; and

- ii. The largest of these similar contracts must be equivalent to at least half of the percentage of the ABC as required above.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

#### 6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

#### 7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that:

[Select one, delete other/s]

- **a.** <u>Subcontracting is allowed. The portions of Project and the maximum percentage</u> <u>allowed to be subcontracted are indicated in the BDS, which shall not exceed twenty</u> <u>percent (20%) of the contracted Goods.</u>
- b. Subcontracting is not allowed.
- 7.2. *[If Procuring Entity has determined that subcontracting is allowed during the bidding, state:]* The Bidder must submit together with its Bid the documentary requirements of the subcontractor(s) complying with the eligibility criteria stated in ITB Clause 5 in accordance with Section 23.4 of the 2016 revised IRR of RA No. 9184 pursuant to Section 23.1 thereof.
- 7.3. [If subcontracting is allowed during the contract implementation stage, state:] The Supplier may identify its subcontractor during the contract implementation stage. Subcontractors identified during the bidding may be changed during the implementation of this Contract.
   Subcontractors must submit the documentary requirements under Section 23.1 of the 2016 revised IRR of RA No. 9184 and comply with the eligibility criteria specified in ITB Clause 5 to the implementing or end user unit.
- 7.4. Subcontracting of any portion of the Project does not relieve the Supplier of any liability or • obligation under the Contract. The Supplier will be responsible for the acts, defaults, and • negligence of any subcontractor, its agents, servants, or workmen as fully as if these were the Supplier's own acts, defaults, or negligence, or those of its agents, servants, or workmen.

#### 8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address stated on **Section I** and/or through videoconferencing/webcasting via Zoom as indicated in paragraph 6 of the **IB**.

#### 9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

#### 10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in **Section VIII (Checklist of Technical and Financial Documents)**.
- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within <u>five</u> <u>vears</u> prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

#### 11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.
- 11.5. [Include if Framework Agreement will be used:] Financial proposals for single or multiyear Framework Agreement shall be submitted before the deadline of submission of bids
   as prescribed in the IB. For multi-year Framework Agreement, evaluation of the financial
   proposal during this stage is for purposes of determining eligibility and whether or not such financial proposal is within the ABC.

#### 12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
  - a. For Goods offered from within the Procuring Entity's country:

- i. The price of the Goods quoted EXW (ex-works, ex-factory, ex-warehouse, exshowroom, or off-the-shelf, as applicable);
- ii. The cost of all customs duties and sales and other taxes already paid or payable;
- iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
- iv. The price of other (incidental) services, if any, listed in the **BDS**.
- b. For Goods offered from abroad:
  - i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
  - ii. The price of other (incidental) services, if any, as listed in the **BDS**.

## 12.2. [*Include if Framework Agreement will be used:*] For Framework Agreement, the following should also apply in addition to Clause 12.1:

#### 

b. For a multi-year Framework Agreement, the prices quoted by the Bidder during submission
of eligibility documents shall be the ceiling and the price quoted during mini- competition
must not exceed the initial price offer. The price quoted during call for mini- competition
shall be fixed during the Bidder's performance of that Call-off and not subject to variation
or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.

#### 13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in:
  - a. Philippine Pesos.

b. *[indicate currency if procurement involves a foreign-denominated bid as allowed by the Procuring Entity, which shall be tradeable or acceptable by the BSP].* 

#### 14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration<sup>1</sup> or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security shall be valid until *120 days*. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.
- 14.3. *[Include if Framework Agreement will be used:]* In the case of Framework Agreement, other than the grounds for forfeiture under the 2016 revised IRR, the bid security may also be forfeited if the successful bidder fails to sign the Framework Agreement, or fails to furnish the performance security or performance securing declaration. Without prejudice on its forfeiture, bid securities shall be returned only after the posting of performance security or performance securing declaration, as the case may be, by the winning Bidder or compliant Bidders and the signing of the Framework Agreement.

#### 15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

#### 16. Deadline for Submission of Bids

- 16.1. The Bidders shall submit on the specified date and time and either at its physical address as indicated in paragraph 7 of the **IB**.
- 16.2. *[Include if Framework Agreement will be used:]* For multi-year Framework Agreement, the submission of bids shall be for the initial evaluation of their technical and financial eligibility. Thereafter, those declared eligible during the said initial eligibility evaluation and entered into a Framework Agreement with the Procuring Entity shall submit anew their best financial offer at the address and on or before the date and time indicated in the Call for each mini-competition.

#### 17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

<sup>&</sup>lt;sup>1</sup> In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance security declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

#### **18. Domestic Preference**

- 18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.
- 18.2. *[Include if Framework Agreement will be used:]* For multi-year Framework Agreement, determination of margin of preference shall be conducted every call for Mini-Competition.

#### **19.** Detailed Evaluation and Comparison of Bids

19.1. The Procuring Entity's BAC shall immediately conduct a detailed evaluation of all Bids rated "*passed*," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.

#### [Include the following options if Framework Agreement will be used:]

- a. In the case of single-year Framework Agreement, the Lowest Calculated Bid shall be determined outright after the detailed evaluation;
- b. For multi-year Framework Agreement, the determination of the eligibility and the compliance • of bidders with the technical and financial aspects of the projects shall be initially made by • the BAC, in accordance with Item 7.4.2 of the Guidelines on the Use of Framework Agreement.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and
   evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the
   · Bid Security as required by ITB Clause 14 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in Section VII (Technical Specifications), although the ABCs of these lots or items are indicated in the BDS for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.
- 19.4. The Project shall be awarded as follows:

#### One Project which shall be awarded as one contract.

19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

#### 20. Post-Qualification

- 20.1. *[Include if Framework Agreement will be used:]* For multi-year Framework Agreement, all bidders initially determined to be eligible and financially compliant shall be subject to initial post-qualification. The BAC shall then recommend the execution of a Framework Agreement among all eligible, technically and financially compliant bidders and the Procuring Entity and shall be issued by HoPE a Notice to Execute Framework Agreement. The determination of the Lowest Calculated Bid (LCB) shall not be performed by the BAC until a Mini-Competition is conducted among the bidders who executed a Framework Agreement. When a Call for Mini-Competition is made, the BAC shall allow the bidders to submit their best financial proposals on such pre- scheduled date, time and place to determine the bidder with the LCB.
- 20.2. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, *{{Include if Framework Agreement will be used:*} or in the case of multi-year Framework Agreement, that it is one of the eligible bidders who have submitted bids that are found to be technically and financially compliant,} the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the BDS. *{{Include if Framework Agreement will be used:*} For every mini-competition in Framework Agreement, the LCB shall likewise submit the required documents for final Post Qualification.}

#### 21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

[Include the following clauses if Framework Agreement will be used:]

- 21.2. At the same time as the Procuring Entity notifies the successful Bidder that its bid has been accepted, the Procuring Entity shall send the Framework Agreement Form to the Bidder, which contract has been provided in the Bidding Documents, incorporating therein all agreements between the parties.
- 21.3. Within ten (10) calendar days from receipt of the Notice to Execute Framework Agreement with the Procuring Entity, the successful Bidder or its duly authorized representative shall formally enter into a Framework Agreement with the procuring entity for an amount of One Peso to be paid to the procuring entity as a consideration for the option granted by the procuring entity to procure the items in the Framework Agreement List when the need arises.
- 21.4. The Procuring Entity shall enter into a Framework Agreement with the successful Bidder within the same ten (10) calendar day period provided that all the documentary requirements are complied with.
- 21.5. The following documents shall form part of the Framework Agreement:
  - a. Framework Agreement Form;
  - b. Bidding Documents;
  - c. Call-offs;

- d. Winning bidder's bid, including the Technical and Financial Proposals, and all other documents/statements submitted (*e.g.*, bidder's response to request for clarifications on the bid), including corrections to the bid, if any, resulting from the Procuring Entity's bid evaluation;
- e. Performance Security or Performance Securing Declaration, as the case may be;
- f. Notice to Execute Framework Agreement; and
- g. Other contract documents that may be required by existing laws and/or specified in the **BDS**.

## Section III. Bid Data Sheet

#### Notes on the Bid Data Sheet

The Bid Data Sheet (BDS) consists of provisions that supplement, amend, or specify in detail, information, or requirements included in the ITB found in Section II, which are specific to each procurement.

This Section is intended to assist the Procuring Entity in providing the specific information in relation to corresponding clauses in the ITB and has to be prepared for each specific procurement.

The Procuring Entity should specify in the BDS information and requirements specific to the circumstances of the Procuring Entity, the processing of the procurement, and the bid evaluation criteria that will apply to the Bids. In preparing the BDS, the following aspects should be checked:

Information that specifies and complements provisions of the ITB must be incorporated.

Amendments and/or supplements, if any, to provisions of the ITB as necessitated by the circumstances of the specific procurement, must also be incorporated.

## **Bid Data Sheet**

ITB Clau se		
5.3	For this purpose, contracts similar to the Project shall be:	
	a. Contract on supply, delivery of various Laboratory/ Technical and Scientific Equipment, and/or customized technical/ medical/ laboratory vehicle or its equivalent	
	<ul> <li><i>b.</i> completed within <u><i>five years</i></u> prior to the deadline for the submission and receipt of bids.</li> </ul>	
7.1	Subcontracting is allowed. The portions of Project and the maximum percentage allowed to be subcontracted are indicated in the BDS, which shall not exceed twenty percent (20%) of the contracted Goods.	
12	The price of the Goods shall be quoted DDP [state place of destination] or the applicable International Commercial Terms (INCOTERMS) for this Project.	
14.1	The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:	
	a. The amount of <i>not less than two percent (2%) of ABC</i> , if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or	
	b. The amount of <i>not less than five percent</i> (5%) of ABC if bid security is in Surety Bond.	
	NOTE: Bidders SHALL use ATTACHED BSWM template of Bid Securing Declaration.	
	Other forms of Bid Securing Declaration will NOT BE ACCEPTED and SHALL BE RATED "FAILED".	
19.4.	The Project shall be awarded as follows:	
	One Project having several items grouped into one lot, which shall be awarded as one contract.	
20.2	[List here any licenses and permits relevant to the Project and the corresponding law requiring it.]	

21.2 [List here any additional contract documents relevant to the Project that may be required by existing laws and/or the Procuring Entity.]	-	ional contract documents relevant to the Project that existing laws and/or the Procuring Entity.]
--	---	--

## Section IV. General Conditions of Contract

#### Notes on the General Conditions of Contract

The General Conditions of Contract (GCC) in this Section, read in conjunction with the Special Conditions of Contract in Section V and other documents listed therein, should be a complete document expressing all the rights and obligations of the parties.

Matters governing performance of the Supplier, payments under the contract, or matters affecting the risks, rights, and obligations of the parties under the contract are included in the GCC and Special Conditions of Contract.

Any complementary information, which may be needed, shall be introduced only through the Special Conditions of Contract.

#### **1.** Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).** 

#### 2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the **SCC**.

#### 3. Performance Security

Within 10 calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.

#### 4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the **SCC**, **Section IV** (**Technical Specifications**) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

#### 5. Warranty

- 5.1 In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 5.2 The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

#### 6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

## Section V. Special Conditions of Contract

#### Notes on the Special Conditions of Contract

Similar to the BDS, the clauses in this Section are intended to assist the Procuring Entity in providing contract-specific information in relation to corresponding clauses in the GCC found in Section IV.

The Special Conditions of Contract (SCC) complement the GCC, specifying contractual requirements linked to the special circumstances of the Procuring Entity, the Procuring Entity's country, the sector, and the Goods purchased. In preparing this Section, the following aspects should be checked:

Information that complements provisions of the GCC must be incorporated.

Amendments and/or supplements to provisions of the GCC as necessitated by the circumstances of the specific purchase, must also be incorporated.

However, no special condition which defeats or negates the general intent and purpose of the provisions of the GCC should be incorporated herein.

## **Special Conditions of Contract**

GCC Clause		
1	Delivery and Documents –	
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:	
	"The delivery terms applicable to this Contract are delivered [indicate place of destination]. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination."	
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).	
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is <i>End-User Representative, Authorized Property Management Unit Personnel and Inspection Committee Member.</i>	
	Supplier shall coordinate with the End-user and Property Management Unit for final schedule of delivery.	
	To schedule the delivery, please click this link or scan the QR code:	
	https://sites.google.com/view/pmu- scheduleofdelivery/home	
	Incidental Services –	
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements:	
	Select appropriate requirements and delete the rest.	
	a. performance or supervision of on-site assembly and/or start-up of the supplied Goods;	

b. furnishing of tools required for assembly and/or maintenance of the supplied Goods;
c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods.
f. [Specify additional incidental service requirements, as needed.]
The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.
Spare Parts –
The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:
Select appropriate requirements and delete the rest.
a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
b. in the event of termination of production of the spare parts:
i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and

ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.

The spare parts and other components required are listed in **Section VI** (**Schedule of Requirements**) and the cost thereof are included in the contract price.

The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of *One Year*.

Spare parts or components shall be supplied as promptly as possible, but in any case, within *not more than Seven Calendar Days* of placing the order.

#### Packaging -

The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

Name of the Procuring Entity

Name of the Supplier

**Contract Description** 

**Final Destination** 

Gross weight

Any special lifting instructions Any special handling instructions
Any relevant HAZCHEM classifications
A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging.
Transportation –
Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price.
Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price.

Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure.

The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Supplier's risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination.

Intellectual Property Rights -

	The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof.
2. 2	N/A
4	The inspections and tests that will be conducted are: <i>Inspection per conformity and compliance to technical specifications</i> .

## Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

ltem Number	Description	Delivered, Weeks/Months
1	Procurement of 1 unit of Mobile Soil Laboratory	Delivery of the Goods is required within 150 Calendar days upon receipt of Notice to Proceed
		Delivery on-site: BSWM NSWRRDC LUPEZ, San Ildefonso, Bulacan

## Section VII. Technical Specifications

#### Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness , and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

#### Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "*or at least equivalent*." References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

# **Technical Specifications**

Item	Specification	Statement of Compliance

[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]

Item No.	Item Description	Quantity	Statement of Compliance
	Supply, Delivery, Modification of vehicle and Installation of		
1	equipment for Mobile Soils Laboratory	1	
	Component I. Commissioning and modification of vehicle to		
	house the required instruments, equipment, and other		
	accessories. (PhP 13,000,000.00)		
	A) Vehicle Specifications:		
	10-wheeler truck, manual transmission, airconditioned		
	Range Power: minimum 280 PS or equivalent		
	RPM Range: minimum 2400 rpm (revolution per minute)		
	Fuel Type: Diesel/Gasoline		
	Torque: maximum 882 Nm (Newton-meter)		
	Gross Weight range: minimum of 26000 Kg (kilogram)		
	Overall Height: maximum of 2940 mm / 9.64 ft		
	Overall Length : minimum 11900 mm / 39.04 ft		
	Payload: minimum 18995 kg, inclusive of trailer		
	Tire: 11R22.5-16PR		
	Wheelbase: minimum 7195 mm / 23.60 ft		
	Engine: 6 Cylinder, In-line, Common-Rail Direct Injection, Blue Power		
	Diesel Engine		
	Rear Body Length: minimum 9754 mm / 32 ft.		
	Inclusive of spare tires (4 pcs) and early warning device		
	Inclusive of vehicle specification plate, engraved		
	Inclusive of Tools for repair:		
	Toolbox, crescent wrenches, vehicle jack, combination wrenches,		
	pliers, vice grips, wire cutter and electrical tape, ratcheting		
	screwdriver set, 3-lb sledgehammer, tire air pressure gauge,		
	flashlights, metal dowel rod, truck trip inspection tool, safety glasses,		
	gloves, crowbar, fuses		
	B) Customization specifications:		
	provision and installation of furnitures, fixtures, and other		
	accessories		
	electrical works, inclusive of convenience outlet, lighting		
	Provision for sample storage cabinet, stainless steel, laminated		
	Office and ICT equipment:		
	Office table (2)- furniture to add antivibration mechanisms /foam		
	cushion capable of withstanding vibration during travel		
	chairs (4)- leather, ergonomic, with seatbelt, embedded / detachable		
	to mobile vehicle		
	Stool (2) - stainless, leather cushion		
	Laboratory Housing Specifications:		

	Length: minimum 32.80 ft / 10000 mm		
	Width: minimum 6.56 ft / 2000 mm		
	Height: minimum 6.56 ft / 2000 mm		
	Three (3) main sections:		
	1) Soil and Water Analysis Section		
	2) Soil Physical Analysis Section		
	3) Soil Microbiological Analysis Section		
	Dimensions per room based on final layout		
	Sample Preparation Area Outside the Laboratory with the following		
	inclusions:		
	10 foldable & collapsible chairs		
	retractable awning or canopy, UV-resistant, waterproof fabric		
	customized size to cover the desired presentation area		
	frame: aluminum or steel		
	mounting: attached securely to the mobile laboratory structure		
	legs or pillars: adjustable for varying terrains and stability		
	with side curtains or screens for additional shade		
	list of fixtures and equipment per section and per unit of Mobile Soil		
	Laboratory is listed below		
	Laboratory fixtures:		
	Standard Laboratory Sink, Stainless steel	3	
	Water Tank, 300 - 500 Liters, stainless steel	1	
	Water suction line with water purifier	1	
	Waste Water Reservoir- 70 L, Either Polytetrafluoroethylene (PTFE)		
	or Polyether ether ketone (PEEK)	1	
	(50 L) Hazardous Waste Storage Containers for acidic, alkaline waste,		
	and metallic waste	3	
	Windows, awning, aluminum frame with glass	3	
	doors		
	-side door (1 swing)		
	-rear door (2 swing)	_	
	provision of collapsible stairs and ramp	2	
	Exhaust fan	2	
	Stainless or Vinyl Flooring, with anti-slippage mechanism		
	Lockable overhead cabinets on either sides, with shelves	6	
	Laboratory tables, chemical resistant tabletop, with drawers and		
	cabinets, antivibration mechanisms /foam cushion capable of		
	withstanding vibration during travel	6	
	Aircon (minimum 2 HP) split type	2	
	Aluminum composite 3mm - outside and Inside wall, Wall insulation		
	(2") chemical and thermal resistant (lot)	1	
	C) Standard inclusions and accessories:		
	truck stabilizer leg (4-legs) with a capacity of at least 2-4 tonnes per		
	leg - Manual (hydraulic)	1	
	Rear and front Camera with storage memory card	2	
	(min of 512 GB)	2	
	CCTV Surveillance System		
	Monitors entrances, exits, and laboratory area;		
	At least 2 units of camera, true IP 66 camera, 1080p or higher		
	resolution, 15 frames per second or greater;		
	Includes centralized recording solution with Video Management		
	Software and Network Video Recorder structured cabling for intranet and internet		
	Scope of work includes installation, testing, and maintenance of		
	CCTV system	1	
	Implement a real-time GPS monitoring system to track the location of	L	
	the Mobile Soils Laboratory at all times. The GPS system should		
	the mobile bons haber atory at an times. The dro system should		
	provide accurate location date even without internet geo-fencing		
	provide accurate location date even without internet, geo-fencing canabilities and canable of generating alerts in case of unauthorized		
	capabilities, and capable of generating alerts in case of unauthorized		
	capabilities, and capable of generating alerts in case of unauthorized movements		
	capabilities, and capable of generating alerts in case of unauthorized movementsEnhance Personnel Access Control by integrating biometric		
	<ul> <li>capabilities, and capable of generating alerts in case of unauthorized movements</li> <li>Enhance Personnel Access Control by integrating biometric authentication for staff operating the Mobile Soils Laboratory. The</li> </ul>		
	capabilities, and capable of generating alerts in case of unauthorized movementsEnhance Personnel Access Control by integrating biometric authentication for staff operating the Mobile Soils Laboratory. The biometric system should support fingerprint or other secure		
	<ul> <li>capabilities, and capable of generating alerts in case of unauthorized movements</li> <li>Enhance Personnel Access Control by integrating biometric authentication for staff operating the Mobile Soils Laboratory. The</li> </ul>		

	m1 . 1 11 1 . 1 1		1
	The system should also include motion sensors, door, window		
	sensors, and central monitoring unit capable of triggering immediate		
	alerts to authorized personnel in the event of security breach		
	Wireless Prepaid Wifi Router		
	2.4 & 5.0 Ghz dual band Wifi- Network Type: 3G and 4G LAN port : 4		
	LAN port		
	With 2 Antenna for stable data transmission No installation, just		
	plug and surf		
	Connect up to 10 devices	2	
	CO2 Fire extinguisher		
	Specification:		
	Classification: C		
	Approximate Weight - 5 lb.	3	
	Dry Chemical Fire Extinguisher		
	Specification:		
	Classification: 40B:C		
	Approximate Weight - 5 lb.	3	
	Power Source:		
	1. Generator - 6-15 kVA, diesel engine		
	movable, can be pulled-out during operation and isolate from main		
	body to avoid vibration on sensitive equipment		
	2. AC (Alternating Current) Power Source - 220-240V, 60Hz		
	3. Solar Panel (alternative power source) at least 6KVA, Hybrid		
1	System		
1	Battery Type: Lithium-ion or Lead-Acid (Deep-Cycle)		
1	Battery Inverter/Charger Capacity: 6kVA		
1	Efficiency: Typically 90% or higher		
	with Battery Management System (BMS)		
	includes circuit breakers or fuses for protection		
	with Battery Disconnect Switch		
	Transfer Switch Electrical Distribution System		
	Registration of LTO (to be registered as government vehicle) and		
	insurance (3 years) inclusive of the following:		
	Commercial invoice or original sales invoice from the country of		
	origin		
	Original sales invoice of body		
	Appropriate COC (Certificate of Coverage)		
	Certified True Copy of DTI-BIS endorsement		
	Original Affidavit of Rebuilt executed by the owner and/or mechanic		
	with the TESDA NC 11 stating, among others, the date of completion		
	Original CSR for engine and chassis		
	Original PNP-HPG MV Clearance Certificate		
	MVIR (Motor Vehicle Inspection Report)		
1	CCES (Certificate of Compliance to Emission Standard)		
	customization of label, design and finish of the mobile soils laboratory		
	according to the DA Branding/ BSWM- NSHP Branding (to be		
1	provided by the End-User during contract implementation)		
	D) After sales services specifications:		
	with five (5) years warranty on parts and services of the vehicle		
·			1
	with end-users training and handbook on operation and maintenance		
	of the vehicle		
	Component II. Provision of laboratory instruments and technical		
	and scientific equipment (PhP 30,000,000.00)		
	Laboratory Equipment List:	Qty	
	A) Soil and Water Analysis		
	pH Meter (Refillable)	2	
	Specifications:		
	pH Range: 0 to 14.00 pH		
	No. of calibration points: at least 3		
	Accuracy: ±0.002 pH		
	With temperature compensation: ATC / MTC		
	Integral Electrode Holder & 100/240 VAC Adapter		
	Power Requirements: 9 V DC adapter, 1.3 A (100/240 VAC, SMPS)		
	Has the ff accessories: 5 pcs pH Electrodes (Refillable), ATC probe	<u> </u>	
1			

Standards	mL each) pH 4,7, 10 NIST Traceable Buffer		
	ectrode refill solution (50 mL)		
Conductivity M		2	
Specifications:			
Range: 0.000 µS	to 1000.0 mS		
Accuracy: ±1 % f			
Resolution: Up to			
Compensation: A			
	ents: 9 V DC adapter, 1.3 A (100/240 VAC, SMPS)		
Power Requirem	ents: 220-240 V, 60Hz		
	able Conductivity Standard Solution, 5 pcs, 147 &		
1413 µS/cm, KCl			
Reciprocating S		1	
Specifications:			
*	Variable speed 60 – 260 osc/min		
Stroke: 1.5" Hori			
Timer: 1min - 6h			
	g: Benchtop, Suction cup feet to prevent creeping		
Payload: min 20			
	box carrier with anti-slide surface and one (1) rubber		
	s available to hold various combinations of beakers,		
flasks, etc			
-	ents: 220-240 V, 60Hz		
	bhotometer w/ laptop and printer	1	
Specifications:	motometer w/ mptop and printer		
	em – Double beam with rear beam access / with		
holmium oxide f			
	r – Double monochromator / Monochromator with		
	and aspheric quartz coated optics		
Source – Xe	ind aspherie quartz couteu opties		
	nge – 190-1100 nm		
	on photodiode detectors for simultaneous		
measurement of			
	$uracy (nm) \pm 0.2$		
	roducibility (nm) < 0.025		
Limiting Resolu			
Spectral bandw	idth 0.1 to 5 nm at 0.01 nm		
Data collection	rate 250 data points per second		
Simultaneous de	termination on multiple wavelengths		
With laptop, Uni	with sipper (5 spare tubings ), 3 extra lamp source		
(Xe Halogen (Tu	ngsten) - D2 Lamp), printer, UV workstation software		
compatible with	equipment, and complete genuine office and OS		
	between sipper and cuvette type		
	ppm NIST Traceable Phosphorus Standard Solution		
	) 500 mL / bottle & 5 pcs Sucrose Standard, NIST		
	ertificate of Analyis, 100g/bottle		
With included la	poratory supplies:		
160 pcs, Borosili	cate test tubes 10 ml test tube and corresponding		
4 pcs 40 placer t	est tube rack (PET)		
Power Requirem	ents: 220-240 V, 60Hz		
Laptop specificat	ions:	1	
Laptop			
-			
Processor: i7-12	h Gen / R7 Zen3+(RDNA2 based) subject to change		
	vare compatibility		
Storage: at least	500GB M.2 PCIe NVMe SSD		
Memory: at least	16GB, DDR4 (upgradable)		
Camera: at least			
Screen size: at le			
Display Type: IP			
Battery Life: at le			
	n: Windows 10/11 Pro subject to change considering		
software compat			
software compat			

	Printer specifications:	1	
	Can print up to Legal size (8.5 x 14 in), color, black		
	Can copy and scan up to A4 size, color, black		
	Has wireless capability		
	Has mobile printing capability		
	Print speed: Black - up to 8 ppm; Color - up to 5 ppm		
	Print quality: Black - up to 1200 x 1200 dpi; Color - up to 4800 x		
	1200 dpi		
	Copy speed: Black - up to 5 cpm; Color - up to 3 cpm		
	Copy resolution: up to 300 x 300 dpi		
	Scan resolution: up to 1200 dpi		
	Paper handling: Input - up to 60 sheets; Output - up to 25 sheets		
	Connectivity: Hi-speed USB; Built-in WiFi 802.11 b/g/n		
	200 - 240 VAC"		
	Single Channel Pipetors Set	1	
	Specifications:		
	Chemically resistant, Fully Autoclavable		
	Volume Adjustable, interchangeable, easy-grip ejector		
	with carousel, 1000 pipette tips per unit		
	Volumes:		
	1000-10,000 μl		
	1000-5000 µl		
	100-1000 μl		
	10-100 μl		
	Bottle Top Dispenser (100 mL)	1	
	Specifications:		
	Capacity: 10-100 mL		
	Subdivision: 10 mL		
	with container bottle (2.5 L) and adapters		
	with recirculation and discharge valve		
	Bottle Top Dispenser (50 mL)	2	
	Specifications:		
	Capacity: 10-50 mL		
	Subdivision: 5.0 mL		
	with container bottle (2.5 L) and adapters		
	with recirculation and discharge valve		
	Centrifuge	1	
	Specifications:		
	Timer range: Up to 9 hr 59 min		
	Electrical Requirements: 220/230V 50/60Hz, 130W		
	Highest Speed, Rpm (Revolutions): minimum 4800		
	Max Rcf, :minimum 5580 x g		
	Setting Type (Revolutions): Variable		
	Tube Sizes (Rotors Offered): 100 mL		
	Rotor capacity: 8 x 100 mL tubes & 8 x 50 mL tubes		
	Horizontal (Rotors Available): 2		
	With centrifuge tube: 100 mL (30 pcs) & 50 mL (30 pcs)		
	Program Storage: minimum 6 programs		
	Display: Large, brightly lit LED display		
	Safety Features: Lid lock, steel armored ring, view port for speed		
	calibration, lid		
	emergency release		
	Block Digester with Scrubber	1	
	Sample positions: 20-40 pcs (100 mL)		
	Maximum Temperature (in °C): 450		
	Digestion vessel size (in ml): 100		
	Maximum Power consumption (in W): 2200		
	A		
	Non-corrosive casing		
	With digestion programs (minimum 100) with auto lift feature		
1	Timer range: Up to 999 min		
	Heater Indication and Warning: LED Display		

1000 pcs Kjeldahl Catalyst Tablets (Contains 1g Na2SO4 And Equivalent Of 0.1g CuSO4 per tablet)		
Nitrogen Distillation Unit	1	
Specifications:	1	
 Measuring range: 0.1-210mg nitrogen		
 Recovery is greater than 99.5% at Nitrogen (N) levels between 1 and		
 210mg		
 Reproducibility: 1% RSD (with the digestion step)		
Distillation time: 3-4 min at 30mg N (6.5 min at 200mg N)		
 Distillation capacity: approx 40mL/min		
Self-adjusting cooling water control		
Waste, Water, and Alkali Reservoir		
With Voltage Regulator		
Power Requirements: 200-240 V, 50-60Hz		
With included laboratory supplies:		
40 pcs (100 mL) digestion and distillation vessel		
125 mL, Borosilicate type Erlenmeyer Flask		
2 pcs 10 ml volumetric pipette		
2 pcs Tris(hydroxymethyl)aminomethane (THAM), NIST Traceable		
with Certificate of Analyis, ≥99% Powder, 100g/bottle		
2 pcs L-lysine Monohydrochloride, NIST Traceable with Certificate of		
Analyis AR, 100g/bottle		
Atomic Absorption Spectroscopy with Laptop	1	
Wavelength range: 185.0 to 900.0 nm	-	
Monochromator: Aberration-corrected Czerny-Turner mounting,		
Number of grating grooves: 1600-1800 lines / mm, Focal length: 330		
 mm		
 Detector: Photomultiplier tube / Solid State Detector		
Optics: Optical double-beam		
Background correction method: BGC-D2 (D2 Hallow Cathode lamp		
method) (185.0 to 430.0 nm)		
Number of turret: at least 8		
Lamp mode: EMISSION, NON-BGC, BGC-D2		
Measurement mode: Flame continuous method, flame emission		
method, flame absorption method		
 Simultaneous determination on multiple wavelengths		
Standard Accessories:		
Autosampler - at least 50 samples w/ Sampling KitCompressor -		
Silent Type		
Nebulizer setup		
Fume Hood / Canopy Hood		
Laptop		
Instrument Grade with Acetylene Gas with tank (3) with Gas Cage	1	
Deuterium Lamp - 3 pcs	1	
Hallow Cathode Lamp (2 per element) : Na, Ca, Mg, K, Fe, Cu, Mn, Zn	1	
AAS Standard Solution corresponding to HCL : 500 mL / bottle	1	
	1	
With included laboratory supplies:	1	
160 pcs, Borosilicate test tubes 10 ml test tube and corresponding		
	1	
4 pcs 40 placer test tube rack (PET)	1	
3 pcs each, 50 mL, 100 ml, and 250 mL Borosilicate Beaker		
5000 mL, PET beaker with handle		
50 pcs 50 mL, Borosilicate type volumetric flask	1	
10 pcs 50 mL, Borosilicate type volumetric flask	1	
50 pcs PET Funnel (Dia: 80 mm, Stem Dia: 8 mm, Stem Length 140	1	
mm)		
5 pcs Filter Paper #42 or equivalent, 125mm dia, ashless	1	
5 pcs filter raper #42 of equivalent, 125min uia, asmess		
100circles/box		
 100circles/boxPower Requirements: 220-240 V, 60Hz		
 100circles/box         Power Requirements: 220-240 V, 60Hz         Laptop specifications:		
 100circles/boxPower Requirements: 220-240 V, 60Hz		
 100circles/box         Power Requirements: 220-240 V, 60Hz         Laptop specifications:         Laptop         -		
 100circles/box         Power Requirements: 220-240 V, 60Hz         Laptop specifications:		

1	Memory: at least 16GB, DDR4 (upgradable)		
	Camera: at least 720p		
	Screen size: at least 15.6-inch		
	Display Type: IPS		
	Battery Life: at least 50WH		
	Operating System: Windows 10/11 Pro subject to change considering		
	software compatibility		
	MS Office: Microsoft Office 2021 (license)		
	Water Deionizer (Type I and Type II)	1	
	Produces both ASTM Type 1 (0.055 uS/cm) and Type 2 (0.067 -0.1		
	uS/cm).		
	Water Purification System, to be attached to Water Tank (300 - 500		
	L) and Reservoir tank (30 mL)		
	RO Flow Rate: 16 L /hr		
	Standard Accessories:		
	main system unit		
	30 L reservoir with recirculation pump, CO2 vent filter and sterile		
	overflow		
	wall bracket accessory		
	Pretreatment system with cartrige		
	RO / pretreatment cartridge		
	reverse osmosis cartridge		
	polishing DI cartridge		
	Ultraviolet lamp		
	inline ultrafilter		
	Additional Accessories (either as standalone or combined):		
	0.1 m polysulfone membrane filter		
	2 pcs - 1 um prefilter		
	2 pcs - hardness stabilizer		
	2 pcs - carbon cartridge		
	2 pcs - RO cartridge		
	2 pcs - Ultrapure cartridge		
	2 pcs - sterile, maximum 0.2 um filter for system		
	2 pcs - CO2 Vent filter		
	2 pcs - CO2 Vent filter Digital Titrator	2	
	Digital Titrator	2	
	Digital Titrator Specifications:	2	
	Digital Titrator Specifications: Nominal Volume: 50 mL	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tube	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tube	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottle	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60Hz		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, Ducted	2	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mm		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mm		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4W		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal design		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow rate		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow ratePower Requirements: 220-240 V, 60Hz	1	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow ratePower Requirements: 220-240 V, 60Hz		
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow ratePower Requirements: 220-240 V, 60HzCross beater millSpecifications:	1	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow ratePower Requirements: 220-240 V, 60HzCross beater millSpecifications:Materials of the grinding tools: hardened steel	1	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow ratePower Requirements: 220-240 V, 60HzCross beater millSpecifications:Materials of the grinding tools: hardened steelMin. sample quantity: 40 - 50 ml	1	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal design With monitoring display for flow ratePower Requirements: 220-240 V, 60HzCross beater millSpecifications:Materials of the grinding tools: hardened steelMin. sample quantity: 40 - 50 mlMax. throughput: approx. 80 L/h	1	
	Digital TitratorSpecifications:Nominal Volume: 50 mLAccuracy in % (±): 0.2%Coefficient of variation (%): 0.1 %PC interface: RS232Accessories:telescoping filling tuberecirculation tubeMinimum 2 batteries3 PP bottle adapters (GL 45/32, GL 45/S 40, GL 32/NS 29/32)2.5 L amber bottlePower Requirements: 220-240 V, 60HzFume Hood, DuctedSpecifications:Maximum of 813mm in width (Overall Size); Work Surface Height:900mm - 1000mmAir Velocity: 0.3~0.8m/s2 units Fluorescent Lamp: 4WBlower: Built-in centrifugal blower, speed adjustableFront Window: Acrylic window; Manual; Reversal designWith monitoring display for flow ratePower Requirements: 220-240 V, 60HzCross beater millSpecifications:Materials of the grinding tools: hardened steelMin. sample quantity: 40 - 50 ml	1	

	Prevents cross contamination, with sieve inlets for >/ = 2mm samples		
	& 0.5 mm samples		
	Standard Accessories:		
	"Bottom sieves made of stainless steel 316L		
	0.5 mm trapezoidal perforation"		
	2 mm trapezoidal perforation		
	universal support stand		
	silent type vacuum cleaner with complete tubings for easy clean up		
	of the unit		
	Dehumidifier	2	
	Specifications:		
	Benchtop style; max speed: approx 4500rpm		
	Extract approx. 20-25L of water per day to maintain humidity below		
	50%		
	Water Tank Volume: minimum 10L		
	Power Requirements: 220-240 V, 60Hz		
	With calibrated thermohygrometer		
	Laboratory Refrigerator (General Use)	1	
	Specifications:		
	Temperature Range: 2~8°C		
	Capacity: Maximum 200 L		
	Refrigerant: CFC free - R290 / R134a / R600a optional		
	Defrost Method: No frost		
	Cooling Type: Forced air cooling		
	Power: 135 W; Power Supply: 220V, 50/60Hz	4	
	Magnetic Stirrer/Hot Plate (Dual)	1	
	Specifications:		
	Speed range: 60 - 1500 rpm		
	Temperature setting range: Ambient - minimum of 350°C		
	Heat and stirring control: Turning knob		
	Power Requirements: 220-240 V, 60Hz		
	Top Loading Balance	1	
	Specifications:		
	Capacity: Minimum 620g		
	Readability : 0.01g		
	Repeatability: 0.02 g		
	Linearity: 0.03 g		
	Power requirement: AC adaptor ( DC12V, 1A )		
	Power Requirements: 220-240 V, 60Hz		
	Vortex Mixer	2	
		2	
	Specifications:		
	Construction material: zinc alloy and technopolymer or equivalent		
	Support system: 4 anti-sliding feet or equivalent		
	Orbital diameter: Maximum 4.5 mm		
-	C 1 4 2000		
	Speed: up to 3000 rpm		
	Operating modes: touch, continuous		
	Operating modes: touch, continuous Power Requirements: 220-240 V, 60Hz		
	Operating modes: touch, continuous Power Requirements: 220-240 V, 60Hz Analytical Balance	1	
	Operating modes: touch, continuous Power Requirements: 220-240 V, 60Hz Analytical Balance Specifications:	1	
	Operating modes: touch, continuous         Power Requirements: 220-240 V, 60Hz         Analytical Balance         Specifications:         Capacity: 220 g	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001g	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 g	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001g	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 g	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002g	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60Hz	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 Hz	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat10 pcs Laboratory spoon/spatula	1	
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat10 pcs Laboratory spoon/spatulaB) Soil Physical		
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat10 pcs Laboratory spoon/spatulaB) Soil PhysicalAutomated Saturated Hydraulic Conductivity System (2 station)		
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat10 pcs Laboratory spoon/spatulaB) Soil PhysicalAutomated Saturated Hydraulic Conductivity System (2 station)with 1 Laptop		
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat10 pcs Laboratory spoon/spatulaB) Soil PhysicalAutomated Saturated Hydraulic Conductivity System (2 station)with 1 LaptopSpecifications:		
	Operating modes: touch, continuousPower Requirements: 220-240 V, 60HzAnalytical BalanceSpecifications:Capacity: 220 gReadability: 0.0001gRepeatability: 0.0001 gLinearity: 0.0002gPower Requirements: 220-240 V, 60HzWith internal calibration functionElectrical requirement: 230V, 60 HzWith the following laboratory supplies:10 packs weighing boat, 100 pcs / packWeighing Boat10 pcs Laboratory spoon/spatulaB) Soil PhysicalAutomated Saturated Hydraulic Conductivity System (2 station)with 1 Laptop		

Sample Ring Inside Cross-Sectional Area: 20.67 cm2		
Reservoir Volume: 930-1000 mL		
Pressure Transducer Range: -100 kPa to +100 kPa Pressure Precision Transducer comes w/ Micro USB cable, Analog		
Ribbon Connector Cable, Software Flash Drive, Instruction Manual Software Application: can control up to 20 independent units		
simultaneously.		
provision for main water reservoir (min capacity: 10L) with		
accessories		
Power Requirements: 220-240 V, 60Hz		
Inclusive of Laptop computer		
Laptop		
•		
Processor: i7-12th Gen / R7 Zen3+(RDNA2 based) subject to change	e	
considering software compatibility		
Storage: at least 500GB M.2 PCIe NVMe SSD		
Memory: at least 16GB, DDR4 (upgradable)		
Camera: at least 720p		
Screen size: at least 15.6-inch		
Display Type: IPS		
Battery Life: at least 50WH		
Operating System: Windows 10/11 Pro subject to change considering	ng	
software compatibility		
MS Office: Microsoft Office 2021 (license)		
Particle Size Analysis System	1	
Includes:		
5pcs Sedimentation Glass Cylinder, 1L		
2 pcs Sodium Hexametaphosphate, AR Grade, 500g		
5 pcs Plastic Pestle		
1 pcPortable Blender		
1pc folding jug; minimum capacity 2.5 Gal.		
Stokes Kit:		
Sieve Set with shaker kit		
Sieve Set :10, 20, 40, 60, 120 and 200		
Sieve Diameter: 3-4 inches		
inclusions: 5 pcs Beaker, yorker spout, drying pans, spatula, timer,		
spoon and gloves		
Soil Sampler Set with Sampling tube	1	
Specifications:	-	
Soil Sampler - 2 sets for the following:		
Soil Sample Shoe		
Handle with beating head		
Hammer with nylon		
Brush and knife set		+
Case (plastic)		
17 sets Sampling tube (100ml)		
Dimensions: I.D.diam.50 x 51mm		
Material: Stainless steel 304		
Quantity: 6 pcs. with 2 lids in a cloth case per set		
2 pcs Shovel		
Tip: Round Shape		
Material: Stainless steel		
weight: <220 grams		
Accessories: Waist band leather case		
Munsell Soil Color Chart	2	
Specifications:		
10R, 10YR, 2.5Y, 2.5YR, 5Y, 5YR, 7.5YR		
10Y-5GY Colors - Olive green		
Gray 1 and 2 (2 separate charts)		
5R individual soil chart		
758 individual soil chart	1	
7.5R individual soil chart		
"New" White page , 7.5R, 10YR, and 2.5Y		
"New" White page , 7.5R, 10YR, and 2.5Y 10Y and 5GY soil chart for glauconitic soils		
"New" White page , 7.5R, 10YR, and 2.5Y		

			1
	- Laminated Hard Cover, Glossy, Ring Binded Cover &		
	Sheets		
	With openings in between chips to allow easy visual		
	comparison with soil samples.		
	Color ships are mounted on neutral gray.		
	-Water-resistant sheets/pages		
	Latest Edition or equivalent		
	Motorized ASTM Liquid Limit Machine		
	with liquid, plastic and shrinkage accessories	1	
	Specifications:		
	with grooving tool, rough brass, with central smooth band 100mm		
	wide		
	Power supply: 210-230V		
	Complete Plastic Limit accessories are Supplied in plastic case		
	Complete Shrinkage Limit accessories are Supplied in plastic case		
	c) Soil Microbiological		
	Carbon Dioxide Respirometer Reader with Laptop and software		
	included	3	
	Specifications:		
	CO2 concentration: up to 200,000 ppm		
	Carbon loss rate: up to 2500 ug/g		
	Operation: standalone assay unit or attached to a compatible laptop		
	unit		
	Power Requirements: 220-240 V, 60Hz		
	Laptop		
	-		
	Processor: i7-12th Gen / R7 Zen3+(RDNA2 based) subject to change		
	considering software compatibility		
	Storage: at least 500GB M.2 PCIe NVMe SSD		
	Memory: at least 16GB, DDR4 (upgradable)		
	Camera: at least 720p		
	Screen size: at least 15.6-inch		
	Display Type: IPS		
	Battery Life: at least 50WH		
	Operating System: Windows 10/11 Pro subject to change considering		
	software compatibility		
	MS Office: Microsoft Office 2021 (license)		
	Temperature detection and recording: Yes		1
	Standard Accessories and Inclusions: Detector, 475 mL jar and 1265		
	mL jar (for larger scale biology studies), 2 O-Rings, USB cable,		
	Software Reader, Instruction Manual, Data logger, and at least 1 yr		
	warranty on parts and service		
	Digital hand held microscope	1	
		1	+
	Specifications:		+
	Flexible Led Control (FLD)		+
	Automatic Magnification Reading (AMR)		
	Magnification: 10X-220X		
	Resolution (2560x1920)		
	Connection type (USB 3.0)		
	Inclusions: Platform stand/holder, Lens cleaner, Cable, Software		
	Root Image Analyzer	1	
	Non-destructive		
	Image resolution: up to 1200 DPI		
	System: Microsoft Windows 7, 8, 10		
	Scan Head Dimensions: 30-40 cm long × 4-5cm diameter		
	Requirements: Tablet with installed software and atleast 1GB		1
	Memory/RAM 1GHZ + Processor		
	Inclusions:		1
	- at least 5 root tubes		
	Root Tube Dimensions:		
	Inner Diameter: atleast 5 cm (5cm min)		
	Outer Diameter: atleast 5 cm (5cm min)		
	Wall Thickness: atleast 3 mm		
	Length: atleast 100 cm		
	Soil Augon		
	- Soil Auger compatible for the root tubes included		

Specifications:	Drying oven	1	
Type: Air of Gravity Convection			
Chamber capacity 30L       Image: Chamber of the external LCD graphic display         Temperature range: Ambient + 10°C to +330°C       Image: Chamber of the external LCD graphic display         Interior: acid-proof stainless steel       Image: Chamber of the external LCD graphic display         Interior: acid-proof stainless steel       Image: Chamber of the external LCD graphic display         Incubator       1         Specifications:       Image: Chamber of the external LCD graphic display         Temperature Binformity (Maximum) : 1 2°C       Image: Chamber of the external LCD graphic display         Temperature Binformity (Maximum) : 1 2°C       Image: Chamber of the external LCD graphic display         Itectrical: 100-240 V, 50 60 Hz       1         Specifications:       1         UV radiation level: Maximum 18 mW / cm2 / sec       Radiation type: Image: Chamber of the external LCD graphic display (maximum)         UV protection: 299.90% Folymethyl methacrylate       UV protection: 299.90% Folymethyl methacrylate         Working area: LGO: Office UV exposure: 1 min-24 hrs / non-stop       UV protection: 299.90% Folymethyl methacrylate         Working area: Addia Comm × 400-600 mm       Vorail dimensions (W-DAII): 560-750 mm × 500-600 mm         Working area: Addia Comm × 400-600 mm       Vorail dimensions (W-DAII): 560-750 mm × 500-600 mm         Working area: Addia Common × 400-600 mm       Vorail dimensions (W-DAII): 500-750 mm × 500-600 mm	*		
Controller, microprocessor with external LCD graphic display         Temperature range: Ambient + 07C to +330°C         Door types solid/door viewing window         Interior acid-proof stathless steel         Power Requirements: 220-240 V, 6011z         Incubator         Specifications:         Specifications:         Temperature Range: Ambient-5°C -70°C         Temperature Range: Ambient-5°C -70°C         Temperature Range: Ambient-5°C -70°C         Temperature Stability: 0.2°C         Shelves: 2-3 layers         Electrical: 100-240 V, 50-60 Hz         Tabletop Laminar Flow         1         Specifications:         UV radiation layer: UV exposure: 1 min-24 hrs / non-stop         UV gradiation type: UV (PSP) Solve Folder         Working area: 645 x 490 mm         Overall dimensions (W-D+DH): 690-750 mm × 500-600 mm         Working area: 645 x 490 mm         Working area: 645 x 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Laboratory Retriggerating Cleareral Use)         Specifications:         Temperature Range: 2-8°C         Capacity: Minimum 200 L         Retrigerant: CPC ree: R290 (R134 / R600a optional         Refrigerant: CPC ree: R290 (R134 / R600a optional         Refrigerant: CPC ree:			
Temperature range: Ambient + 10°C to + 33°C       Interior: acid pyroof stainless steel       Housing: power coarde sheet       Power Requirements: 220-240 V, 601½       Incubator       Specifications:       Temperature Range: Ambient 5°C - 70°C       Temperature Bunker Multimeter       Specifications:       Betwees 2-3 layers       Electrical: 100-240 V, 50-60 Hz       Tableop Laminar Flow       1       Specifications:       IV radiation level: Maximum 18 mW / cm2 / sec       Radiation type: UV (A = 253.7 mL), coone-free       Poglial time setting of larcet UV exports: 1 min-24 hrs / non-stop       UV protection: >99.90% Polymethyl methacrylate       Working area: 1.60.70mm x ¥ Mol-600 mm       Working area: 6.60 v 490 mm       Working area: 6.60 v 490 mm       Working area: 6.50 v 490 mm       Working area: 6.50 v 490 mm       Nomial operating toxing: 100-240 V, 50/6011z       Laboratory Refrigerator (General Use)       1       Specifications:       1       Power Stapping Provider 111-244 / R600a optional       Power Supping Provence: 6.11/6.30 PA       Power Supping Provence: 6.11/6.30 PA<			
Door type: solid/door viewing window         Interior side/poor stalless steel           Ilousing: power coated sheet         Ilousing: power coated sheet           Power Requirements: 220-240 V, 60Hz         Ilousing: power coated sheet           Specifications:         I           Temperature Range: Ambient-5°C -70°C         Ilousing: power coated sheet           Temperature Stability: 0.2°C         Ilousing: power coated sheet           Temperature Stability: 0.2°C         Ilousing: power coated sheet           Shelves: 2-3 layers         Ilousing: power coated sheet           Electrical: 100-240 V, 50-60 Hz         Ilousing: power coated sheet           Tabletop Laminar Flow         I           Radiation type: UV (-2 V, 50-60 Hz         Ilousing: power coated sheet           Working area: 16.00-700mm mW / cm2 / sec         UV production: se99 09/90 Polymethylin methacrylate           Working area: 16.00-700mm W 400-500 mm         Sourcing           Overall dimensions (W-DH): 690-750mm × 500-600 mm         Ilousing power coated sheet           Working area: 645 x 490 mm         Ilousing power coated sheet           Nominal operating voltage: 100-240 V, 50/60 Hz         Ilousing power sheet           Laboratory Refrigerator (General Use)         1           Specifications:         Ilousing Ilousin			
Interior: acid proof stabiless stel			
Housing: power coated sheet         Incubator           Power Requirements: 220-240 V, 601z         1           Specifications:         1           Specifications:         1           Temperature Requirements: 20-260 V, 50-60 Hz         1           Tabletop Laminar Flow         1           Tabletop Laminar Flow         1           Radiation type: 1V (a 2533 run), azone-free         1           Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop         1           UV radiation level: Maximum 18 mW / cm2 / sec         1           Working area: 1.600-700mm × 400-500 mm         1           Overall dimensions (W+D+H); 690-750 mm × 500-600 mm × 500-600 mm         1           Working area: 4.60 × 490 mm         1           Working area: 645 × 490 mm         1           Nominal operating voltage: 100-240 V, 50/60Hz         1           Laboratory Refrigerator (General Use)         1           Temperature Range: 2-49°C         1           Capacity: Minimum 200 L         1           Refrigerator: CGeneral Use)         1           Power: 135 W; Power Supply: 220V, 50/60Hz         1           Dore: Manual, Automatic         1           Specifications:         1           Specifications:         1			
Power Requirements: 220-240 V, 60Hz         1           Specifications:         1           Specifications:         1           Temperature Bange: Ambient+5°C -70°C         1           Temperature Stability: ±0.2°C         1           Specifications:         1           Specifications:         1           Specifications:         1           Specifications:         1           Specifications:         1           Specifications:         1           Optimation level: Maximum 18 mV / cm2 / sec         1           Badiation type: UV (A = 253.7 nm), ozone-free         1           Digital time setting of direct UV exposure: 1 nin-24 hrs / non-stop         1           UV protection: >99.90% Polymethyl methacrylate         1           Working area: 455 × 490 mm         0           Working area: 645 × 490 mm         1           Nominal operating voltage: 100-240 V, 50/60Hz         1           Specifications:         1           Specifications:         1           Specifications:         1           Specifications:         1           Specifications:         1           Cooling         1           Power: 135 W; Power Supply; 220V, 50/60Hz         1			
Incubator         1           Specifications:			
Specifications:		1	
Temperature Range: Ambient+5°C. 70°C         Temperature Stability: ±0.2°C         Shelves: 2-3 layers         Electrical: 100-240 V, 50-60 Hz         Tabletop Laminar Flow         1         Specifications:         UV radiation type: UV (A = 253.7 nm), ozone-free         Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop         UV protection: >99.90% Polymethyl methacrylate         Working area: 1. 60.7-00m x + W 400-500 mm         Overall dimensions (W×D×H): 690-750mm × 500-600m × 500-6000 mm         mm         Working area: 1. 60.7-00m x + W 400-500 mm         Working area: 645 x 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Refrigerant: CFC free: R290 / R134a / R600a optional         Defrost Methad: No frost         Coajing Type: Forced air cooling         Coajing Type: Forced air cooling         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         Capacity: maximum 241.         Door: Manual, Automatic         Designed Pressure: 0-1/0.3MPa         Designed			
Temperature Uniformity(Maximum): ±1.2°C     Image: State S	*		
Temperature Stability: 60.2°C         Shelves: 2-3 Jayers         Electrical: 100-240 V, 50-60 Hz         Tabletop Laminar Flow         1         Specifications:         UV radiation level: Maximum 18 mW / cm2 / sec         Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop         UV protection: >99.90% Polymethyl methacrylate         Working area: 1.600-700mm × 0400-500 mm         Overall dimensions (W-Dv1): 690-750mm × 500-600         mm         Working area: 645 × 490 mm         Working area: 645 × 490 mm         Working area: 645 × 490 mm         Nomial operating voltage: 100-240 V, 50/60Hz         Laboratory Refrigerator (General Use)         1         Specifications:         Temperature Range: 2-8°C         Capacity: Minimum 2001.         Refrigerati: CFC (Free - R2290 / R134 a / R600a optional         Defrost Method: No frost         Cooling Type: Force dair cooling.         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         2         Capacity: maximum 24L         Door: Manual, Automatic         Designed Pressure: 0.1/0.3MPa         Designed Pressure: 0.1/0.3MPa			
Shelves: 2-3 Juyers			
Flectrica: 100-240 V, 50-60 Hz     1       Tabletop Laminar Flow     1       Specifications:     1       UV radiation level: Maximum 18 mW / cm2 / sec     1       Badiation type: UV (2 = 253.7 nm), ozone-free     1       Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop     1       UV pratection: >99.0% Polymethy methacrylate     1       Working area: 1.600-700mm × W 400-500 mm     1       Overall dimensions (W×D×H): 690-750mm × 500-600m m × 500-600     1       Working surface material: Steel with chemicals resistant powder     1       coating     1     1       Working area: 645 × 490 mm     1       Nomial operatury volage: 100-240 V,50/601z     1       Laboratory Refrigerator (General Use)     1       Specifications:     1       Temperature Range: 2-8°C     2       Capacity: Minimum 200 L     1       Refrigerato: CFC free + R290 / R134a / R600a optional     1       Defrost Method: No fost     1       Cooling Type: Forced air cooling     1       Power: 135 W; Power Supply: 220V, 50/60Hz     1       Tabletop Autoclave     1       Specifications:     1       Capacity: maximum 241.     2       Door: Manula, Automatic     2       Designed Pressure: -0.1/0.3MPa     2       Warking T			
Tabletop Laminar Flow     1       Specifications:     1       UV radiation level: Maximum 18 mW / cm2 / sec     1       Radiation type : UV (\u03e9 25.3.7 mm), ozone-free     1       Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop     1       UV protection: >99.90% Polymethyl methacrylate     1       Working area:: 1.60.700mm × 400-500 mm     1       Overall dimensions (W×D>H): 690-750mm × 500-600 mm     1       Working surface material: Steel with chemicals resistant powder     2       coating     1       Working area:: 645 × 490 mm     1       Nominal operating voltage: 100-240 V, 50/60Hz     1       Laboratory Refrigerator (General Use)     1       Specifications:     1       Temperature Range: 2~8°C     1       Capacity: Minimu 200 L     1       Refrigerant: CPC free - R290 / R134a / R600a optional     1       Defrost Method: No frost     1       Cooling Type: Forced air cooling     1       Power: 135 W; Power Supply: 220V, 50/60Hz     1       Specifications:     1       Specifications:     1       Specifications:     1       Specifications:     1       Copacity: maximum 24L     1       Door: Manual, Automatic     1       Designed Pressure: -0.1/0.3MPa     1			
Specifications:		1	
IV radiation level: Maximum 18 mW / cm2 / sec         Radiation level: Maximum 18 mW / cm2 / sec         Bigital time setting of direct UV exposure: 1 min-24 hrs / non-stop         UV protection: >99.90% Polymethyl methacrylate         Working area: 1.600-700m xW 400-500 mm         Overall dimensions (W×D×H): 690-750mm × 500-600 mm         Working area: 1.600-700m xW 400-500 mm         Working area: 645 × 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Laboratory Refrigerator (General Use)         1         Specifications:         7         Temperature Range: 2~8°C         Capacity: Minimum 200 L         Refrigerant: CFC free - R290 / R134a / R600a optional         Defrost Method: No frost         Cooling Type: Forced air cooling         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         Capacity: maximum 24L         Door: Manual, Automatic         Designed Pressure: -01/0.3MPa         Water Tank Volume: maximum 35L         Water Tank Volume: maximum 35L         Water Tank Volume: maximum 35L         Working Temp: 12-1134°C         Vacuum system: High efficiency vacuum pump         Atmospheric Pressure: 76~106 kpa <tr< td=""><td></td><td>1</td><td></td></tr<>		1	
Radiation type : UV (\$ = 253.7 mJ), zoone-free         Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop         UV protection: >99.90% Polymethyl methacrylate         Working area: L 600-700mm × W 400-500 mm         Overall dimensions (WxD+H): 690-750mm × 500-600 mm × 500-600 mm         Working surface material: Steel with chemicals resistant powder         coating         Working area: 645 × 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Laboratory Refrigerator (General Use)         Specifications:         Temperature Range: 2~8°C         Capacity: Minimum 200 I.         Refrigeratic CF fore - R290 / R134a / R600a optional         Defrost Method: No frost         Cooling Type: Forced air cooling         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         2         Capacity: maximum 24L         Door: Manual, Automatic         Designed Pressure: -0.1/0.3MPa         Water Tank Volume: maximum 3.5L         Water Tank Volume: maximum 3.5L         Water Tank Volume: Tomp: 5-40°C         Standard Accessories: USB/Printer         Power supply: 220V         Consumption: 3kVA         Maximum weight: 65 kg <t< td=""><td></td><td></td><td></td></t<>			
Digital time setting of direct UV exposure: 1 min-24 hrs / non-stop         UV protection: >9.90% Polymethyl methacrylate         Working area: 1.600-700mm × W 400-500 mm         Overall dimensions (WxD×H]: 690-750mm × 500-600 mm         Working surface material: Steel with chemicals resistant powder coating         Working area: 645 × 490 mm         Nominal operating voltage: 100-240 v, 50/60Hz         Laboratory Refigerator (General Use)         1         Specifications:         Temperature Range: 2~8°C         Capacity: Minimum 200 L         Refrigerant: CFC free - R290 / R134a / R600a optional         Defrost Method: No frost         Cooling Type: Forced air cooling         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         Capacity: maximum 24L         Door: Manual, Automatic         Designed Pressure: -0.1/0.3MPa         Water Tank Volume: maximum 35L         Working Temp: 121-134*C         Vacuum system: High efficiency vacuum pump         Armbient Temp: 5~40°C         Standard Accessories: USB/Printer         Power supply: 220V         Consumption: 3kVA         Maximum weight: 65 kg         Single Chanel Pipetors         Sp			
UV protection: >99.90% Polymethyl methacrylate         Working area: L 600-700mm × W 400-500 mm         Overall dimensions (WxDxH): 690-750m × 500-600mm × 500-600 mm         Working surface material: Steel with chemicals resistant powder         coating         Working area: 645 × 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Laboratory Refrigerator (General Use)         1         Specifications:         Temperature Range: 2~8°C         Capacity: Minimum 200 I.         Refrigerant: CFC free - R290 / R134a / R600a optional         Defrost Method: No frost         Cooling Type: Forced air cooling         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         Capacity: maximum 24L         Door: Manual, Automatic         Designed Pressure: -0.1/0.3MPa         Wark Tank Volume: maximum 3.SL         Working Temp: 121-134*C         Vacuum system: High efficiency vacuum pump         Atmospheric Pressure: 5~106 kpa         Anmbient Temp: 5-40*C         Standard Accesories: USB/Printer         Power supply: 220V         Consumption: 3kVA         Maximum weight: 65 kg         Single Chanel Pipetors       1			
Working area: L 600-700mm × W 400-500 mm         Overall dimensions (W×D×H): 690-750mm × 500-600 mm         mm         Working surface material: Steel with chemicals resistant powder         coating         Working area: 645 × 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Laboratory Refrigerator (General Use)         1         Specifications:         Capacity: Minimum 200 L         Refrigerant: CFC free - R290 / R134a / R600a optional         Defrost Method: No frost         Cooling Type: Forced air cooling         Power: 135 W; Power Supply: 220V, 50/60Hz         Tabletop Autoclave         1         Specifications:         Capacity: maximum 24L         Door: Manual, Automatic         Door: Manual, Automatic         Designed Pressure: -0.1/0.3MPa         Wart Tank Volume: maximum 35L         Working Temp: 121-134°C         Vacuum system: High efficiency vacuum pump         Atmospheric Pressure: 76 - 106 kpa         Ambient Temp: 5-40°C         Standard Accessories: USB/Printer         Power supply: 220V         Consumption: 3kVA         Maximum weight: 65 kg         Single Chanel Pipetors         Single Chanel Pipetors			
Overall dimensions (W×D×H): 690-750mm × 500-600 mm         Working surface material: Steel with chemicals resistant powder coating         Working area: 645 × 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz         Laboratory Refrigerator (General Use)         1         Specifications:         Temperature Range: 2~8°C         Capacity: Minimum 200 L         Refrigerant: CPC free - R290 / R134a / R600a optional         Defrost Method: No frost         Cooling Type: Forced air cooling         Power: 135 W; Power Suply: 220V, 50/60Hz         Tabletop Autoclave         Door: Manual, Automatic         Designed Pressure: -0.1/0.3MPa         Water Tank Volume: maximum 3.5L         Working Temp: 121-134*C         Vacuum system: High efficiency vacuum pump         Atmospheric Pressure: 76~106 kpa         Ambient Temp: 5~40°C         Standard Accessories: USB/Printer         Power supply: 220V         Consumption: 3kVA         Maximum weight: 65 kg         Single Chanel Pipetors         Single Chanel Pipetors         Single Chanel Pipetors         Moximum weight: 65 kg         Single Chanel Pipetors         Chemically resistant and fully autoclavable         Volume Adjustable, interchang			
mm       Working surface material: Steel with chemicals resistant powder         coating       Working area: 645 × 490 mm         Nominal operating voltage: 100-240 V, 50/60Hz       1         Laboratory Refrigerator (General Use)       1         Specifications:       1         Temperature Range: 2~8°C       1         Capacity: Minimum 200 L       Refrigerant: CPC free - R290 / R134a / R600a optional         Defrost Method: No frost       1         Cooling Type: Forced air cooling       1         Power: 135 W; Power Supply: 220V, 50/60Hz       1         Specifications:       1         Capacity: maximum 24L       1         Door: Manual, Automatic       1         Designed Pressure: -0.1/0.3MPa       1         Water Tank Volume: maximum 3.5L       1         Working Temp: 121-134°C       1         Vacuum system: High efficiency vacuum pump       1         Atmospheric Pressure: 76~106 kpa       1         Ambient Temp: 5~40°C       1         Standard Accessories: USB/Printer       1         Power supply: 220V       1         Consumption: 3kVA       1         Maximum weight: 65 kg       1         Single Chanel Pipetors       1         Specifications: <td< td=""><td></td><td></td><td></td></td<>			
Working surface material: Steel with chemicals resistant powder coating			
coatingImage: coatingWorking area: 645 × 490 mmImage: coating voltage: 100-240 V, 50/60HzLaboratory Refrigerator (General Use)1Specifications:Image: coatingTemperature Range: 2~8°CImage: coatingCapacity: Minimum 200 LCapacity: Minimum 200 LRefrigerant: CFC free - R290 / R134a / R600a optionalImage: coatingDefrost Method: No frostImage: coatingCooling Type: Forced air coolingImage: coatingPower: 135 W; Power Supply: 220V, 50/60HzImage: coatingTabletop Autoclave1Specifications:Image: coatingCapacity: maximum 24LImage: coatingDoor: Manual, AutomaticImage: coatingDoor: Manual, AutomaticImage: coatingWater Tank Volume: maximum 3.5LImage: coatingWater Tank Volume: maximum 3.5LImage: coatingWater Stank OrderImage: coatingAtmospheric Pressure: 76-106 kpaImage: coatingAtmospheric Pressure: 76-106 kpaImage: coatingAmbient Termp: 5-x40°CImage: coatingSingle Chanel Pipetors1Single Chanel PipetorsImage: coatingConsumption: 3kVAImage: coatingVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 opiett tips per unitVolumes:100-1000 µl100-1000 µlImage: coating100-1000 µlImage: coating100-1000 µlImage: coating100-1000 µlImage: coating100-1000 µlImage: coating100-1000 µlI			
Working area: 645 × 490 mm       Image: 100-240 V, 50/60Hz         Laboratory Refigerator (General Use)       1         Specifications:       1         Temperature Range: 2-8°C       1         Capacity: Minimum 200 L       1         Refrigerant: CFC free - R290 / R134a / R600a optional       1         Defrost Method: No frost       1         Cooling Type: Forced air cooling       1         Power: 135 W: Power Supply: 220V, 50/60Hz       1         Specifications:       1         Capacity: maximum 24L       1         Door: Manual, Automatic       1         Designed Pressure: -0.1/0.3MPa       1         Warking Temp: 121-134°C       1         Vacuum system: High efficiency vacuum pump       1         Atmospheric Pressure: 5-106 kpa       1         Ambient Temp:: 5~40°C       1         Standard Accessories: USB/Printer       1         Power supply: 220V       1         Consumption: 3kVA       1         Maximum weight: 65 kg       1         Specifications:       1         Chemically resistant and fully autoclavable       1         Volume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unit       1000-5000 µl         1000-1000			
Nominal operating voltage: 100-240 V, 50/60Hz       1         Laboratory Refrigerator (General Use)       1         Specifications:	 		
Laboratory Refrigerator (General Use)1Specifications:Temperature Range: 2-8°CCapacity: Minimum 200 LRefrigerant: CFC free - R290 / R134a / R600a optionalDefrost Method: No frostCooling Type: Forced air coolingPower: 135 W; Power Supply: 220V, 50/60HzTabletop Autoclave1Specifications:Capacity: maximum 24LDoor: Manual, AutomaticDesigned Pressure: -0.1/0.3MPaWater Tank Volume: maximum 3.5LWater Tank Volume: maximum 3.5LWorking Temp: 121-134°CAtmospheric Pressure: 76~106 kpaAtmospheric Pressure: 76~106 kpaAtmospheric Pressure: 56~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel Pipetors1Specifications:Chemically resistant and fully autoclavableVolumes:1000 pipette tips per unitVolumes:1000-10,000 µl1000-1000 µl100-1000 µl			
Specifications:       Image: 2~8°C         Capacity: Minimum 200 L       Refrigerant: CFC free - R290 / R134a / R600a optional         Defrost Method: No frost       Image: Refrigerant: CFC free - R290 / R134a / R600a optional         Defrost Method: No frost       Image: Refrigerant: CFC free - R290 / R134a / R600a optional         Power: 135 W; Power Supply: 220V, 50/60Hz       Image: Refrigerant: CFC free - R290 / R134a / R600a optional         Tabletop Autoclave       1         Specifications:       Image: Refrigerant: CFC free - R290 / R134a / R600a optional         Door: Manual, Automatic       Image: Refrigerant: CFC free - R290 / R134a / R600a optional         Door: Manual, Automatic       Image: Refrigerant: CFC free - R290 / R134a / R600a optional         Water Tank Volume: maximum 3.5L       Image: Refrigerant: CFC free - R290 / R134a / RC         Water Tank Volume: maximum 3.5L       Image: Refrigerant:		1	
Temperature Range: 2~8°C		1	
Capacity: Minimum 200 LRefrigerant: CFC free - R290 / R134a / R600a optionalDefrost Method: No frostCooling Type: Forced air coolingPower: 135 W; Power Supply: 220V, 50/60Hz1Tabletop Autoclave1Specifications:Capacity: maximum 24LDoor: Manual, AutomaticDesigned Pressure: -0.1/0.3MPaWater Tank Volume: maximum 3.5LWorking Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp:. 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel Pipetors1Specifications:Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes:1000-10,000 µl1000-10,000 µl20-200ul10-100 µl20-200ul	1		
Refrigerant: CFC free - R290 / R134a / R600a optionalDefrost Method: No frostCooling Type: Forced air coolingPower: 135 W; Power Supply: 220V, 50/60HzTabletop Autoclave1Specifications:Capacity: maximum 24LDoor: Manual, AutomaticDesigned Pressure: -0.1/0.3MPaWater Tank Volume: maximum 3.5LWorking Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp: 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel PipetorsChemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-100 µl20-2000l10-100 µl20-2000l10-100 µl			
Defrost Method: No frostCooling Type: Forced air coolingPower: 135 W; Power Supply: 220V, 50/60HzTabletop Autoclave1Specifications:Capacity: maximum 24LDoor: Manual, AutomaticDesigned Pressure: -0.1/0.3MPaWater Tank Volume: maximum 3.5LWorking Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp: 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel PipetorsChemically resistant and fully autoclavableVolumes:1000 pipette tips per unitVolumes:1000-10.000 µl20-200ul <tr< td=""><td></td><td></td><td></td></tr<>			
Cooling Type: Forced air coolingPower: 135 W; Power Supply: 220V, 50/60HzTabletop AutoclaveSpecifications:Capacity: maximum 24LDoor: Manual, AutomaticDesigned Pressure: -0.1/0.3MPaWater Tank Volume: maximum 3.5LWorking Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAtmospheric Pressure: 76~106 kpaAtmospheric Pressure: 0.5 kgConsumption: 3kVAMaximum weight: 65 kgSingle Chanel PipetorsChemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-1000 µl 20-200ul10-100 µl20-200ul 			
Power: 135 W; Power Supply: 220V, 50/60Hz1Tabletop Autoclave1Specifications:Capacity: maximum 24LDoor: Manual, AutomaticDesigned Pressure: -0.1/0.3MPaWater Tank Volume: maximum 3.5LWorking Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp:. 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel Pipetors1Specifications:Chemically resistant and fully autoclavableVolume s: 1000 pipette tips per unitVolumes: 1000-10,000 µl 100-1000 µl 20-200ul 10-100 µlAutol µlA			
Tabletop Autoclave1Specifications:			
Specifications:Image: specification specificati			
Capacity: maximum 24LImage: Capacity: maximum 24LDoor: Manual, AutomaticImage: Capacity: maximum 3.5LWater Tank Volume: maximum 3.5LImage: Capacity: Capacity		1	
Door: Manual, AutomaticImage: Second Se			
Designed Pressure: -0.1/0.3MPaImage: Constraint of the system of the syste			
Water Tank Volume: maximum 3.5LWorking Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp:: 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel PipetorsSpecifications:Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-10,000 µl 20-200ul 10-100 µl20-200ul 10-100 µl			
Working Temp: 121-134°CVacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp.: 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel PipetorsSpecifications:Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-10,000 µl 20-200ul 10-100 µl20-200ul 10-100 µl			
Vacuum system: High efficiency vacuum pumpAtmospheric Pressure: 76~106 kpaAmbient Temp.: 5~40°CStandard Accessories: USB/PrinterPower supply: 220VConsumption: 3kVAMaximum weight: 65 kgSingle Chanel PipetorsSpecifications:Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-10,000 µl 100-5000 µl 20-200ul 10-100 µl			
Atmospheric Pressure: 76~106 kpa			
Ambient Temp.: 5~40°CIStandard Accessories: USB/PrinterIPower supply: 220VIConsumption: 3kVAIMaximum weight: 65 kgISingle Chanel Pipetors1Specifications:IChemically resistant and fully autoclavableIVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitIVolumes: 1000-10,000 µl 100-1000 µl 20-200ul 10-100 µlI			
Standard Accessories: USB/Printer			
Power supply: 220VImage: Consumption: 3kVAMaximum weight: 65 kgImage: Chanel PipetorsSingle Chanel Pipetors1Specifications:Image: Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitImage: Chemically resistant and fully autoclavableVolumes: 1000-10,000 µl 1000-5000 µl 20-200ul 100-1000 µlImage: Chemically resistant and fully autoclavable			
Consumption: 3kVAImage: Consumption: 3kVAMaximum weight: 65 kg1Single Chanel Pipetors1Specifications:Image: Chemically resistant and fully autoclavableChemically resistant and fully autoclavableImage: Chemically resistant and fully autoclavable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes:Image: Chemically resistant and fully autoclavableImage: Construct of the problem of			
Maximum weight: 65 kgSingle Chanel PipetorsSpecifications:Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-10,000 μl 1000-5000 μl 100-1000 μl 20-200ul 10-100 μl			
Single Chanel Pipetors1Specifications:Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitVolumes: 1000-10,000 μl 1000-5000 μl 100-1000 μl 20-200ul 10-100 μl	*		
Specifications:Image: Chemically resistant and fully autoclavableVolume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unitImage: Chemically resistant and fully autoclavableVolumes: 1000-10,000 μl 1000-5000 μl 100-1000 μl 20-200ul 10-100 μlImage: Chemically resistant and fully autoclavable			
Chemically resistant and fully autoclavable       Chemically resistant and fully autoclavable         Volume Adjustable, interchangeable, easy-grip ejector, with carousel,       1000 pipette tips per unit         Volumes:       1000-10,000 µl         1000-5000 µl       1000-5000 µl         20-200ul       10-100 µl         10-100 µl       100-100 µl		1	
Volume Adjustable, interchangeable, easy-grip ejector, with carousel, 1000 pipette tips per unit         Interchangeable, easy-grip ejector, with carousel,           Volumes:         1000-10,000 µl         1000-5000 µl           1000-5000 µl         100-1000 µl         100-1000 µl           20-200ul         10-100 µl         100-100 µl			
1000 pipette tips per unit           Volumes:           1000-10,000 µl           1000-5000 µl           100-1000 µl           20-200ul           10-100 µl			
Volumes:         1000-10,000 μl           1000-5000 μl         100-1000 μl           20-200ul         10-100 μl	Volume Adjustable, interchangeable, easy-grip ejector, with carousel,		
1000-10,000 μl       1000-5000 μl         100-1000 μl       20-200ul         10-100 μl       10-100 μl	 1000 pipette tips per unit		
1000-5000 μl         100-1000 μl         20-200ul         10-100 μl			
100-1000 μl 20-200ul 10-100 μl	1000-10,000 μl		
20-200ul 10-100 μl	•		
10-100 µl			
d) Standard inclusions:			
	 d) Standard inclusions:		

	in the size of UDC for an air international state of the second st	
	inclusive of UPS for various sensitive equipment:	
	UV-Vis	
	AAS Gross Baster Mill	
	Cross Beater Mill	
	Carbon Dioxide Respirometer Reader	
	Motorized ASTM Liquid Limit Machine	
	To include the following 5 pcs each of certified reference material	
	(CRM) and History Proficiency Test Material / quality reference	
	material (QRM)	
	Certified Reference Material for Agricultural Environment, Soil,	
	175g/bottle, Sandy Soil, Attach Certificate of Analysis (Must have	
	NIST Traceability)	
	Soil parameters are the following but not limited to:	
	-Phosphorus (Olsen and Bray 1 Method)	
	-Exchangeable Bases Ammonium Acetate Extraction Method for	
	Potassium, Sodium, Calcium and Magnesium	
	-Trace Elements DTPA Extraction Method for Zinc, Manganese,	
	Copper and Iron	
	- Soil pH (1:1 Ratio)	
	- Soil Electrical Conductivity (1:1 Ratio)	
	- Organic Matter (Walkley-Black Method)	
	- Total Nitrogen (Kjeldahl Method)	
	History Proficiency Test Samples (Quality Reference Material) for Soil	
	Chemistry and Physical Parameters; 4 samples per set, 1kg/bottle,	
	with analysis report	
	Soil Parameters are the following but not limited to:	
	- Soil Electrical Conductivity (1:1 Soil-to-Water Ratio)	
	- Soil pH (1:1 Soil-to-Water Ratio)	
	- Available Phosphorus (Olsen and Bray Method)	
	- Exchangeable Bases Ammonium Acetate Extraction Method for	
	Potassium, Sodium, Magnesium and Calcium	
	- Trace Elements DTPA Extraction Method (Iron, Copper, Zinc and	
	Manganese)	
	- Soil Total Nitrogen (Kjeldahl)	
	- Soil Organic Matter (Walkley-Black)	
	- Cation Exchange Capacity	
	- Particle Size Analysis (Sand, Silt and Clay)	
	includes provisions to ensure storage and safety of equipment during	
	transport (e.g. fixtures, dampening pads, antivibration pad,	
	equipment brace, plexi glass.)	
	with Calibration Certificate from Competent Calibration Laboratory	
	(PAB Accredited Calibration Laboratory or with Statement of	
	Metrology)	
	e) After sales services specifications:	
	Inclusive: Commissioning and installation of all required instruments,	
	equipment, and other accessories.	
	With end-users training and handbook on operation and maintenance	
	of all instruments	
	Providing technical back-up (monitoring and trouble shooting) and	
	after-sales services and guidance for improving the efficiency of the	
	lab	
	Calibration, standardization & operation of all instruments	
	with standard five years warranty on parts and services (calibration	
L	and preventive maintenance) for all equipment	
	with insurance coverage for all technical and scientific equipment (at	
	least 5 years)	
	Submission to include proposed floor plan for the Mobile Soil	
	Laboratory, subject for approval of the BSWM during the contract	
	implementation.	
	Compliance with Section VI. Schedule of Requirements	
L		

# Section VIII. Checklist of Technical and Financial Documents

# Notes on the Checklist of Technical and Financial Documents

The prescribed documents in the checklist are mandatory to be submitted in the Bid, but shall be subject to the following:

GPPB Resolution No. 09-2020 on the efficient procurement measures during a State of Calamity or other similar issuances that shall allow the use of alternate documents in lieu of the mandated requirements; or

Any subsequent GPPB issuances adjusting the documentary requirements after the effectivity of the adoption of the PBDs.

The BAC shall be checking the submitted documents of each Bidder against this checklist to ascertain if they are all present, using a non-discretionary "pass/fail" criterion pursuant to Section 30 of the 2016 revised IRR of RA No. 9184.

# **Checklist of Technical and Financial Documents**

	Class "A" Documents
<u>Legal I</u>	<u>Documents</u>
(a)	Valid PhilGEPS Registration Certificate (Platinum Membership) (all page in accordance with Section 8.5.2 of the IRR;
Technie	cal Documents
(b)	Statement of the prospective bidder of all its ongoing government and privac contracts, including contracts awarded but not yet started, if any, wheth similar or not similar in nature and complexity to the contract to be bid; and
(c)	Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid, except under conditions provided for in Sections 23.4.1.3 and 23.4.2.4 of the 2016 revised IRR of RA No. 9184, within the relevant period as provided in the Bidding Documents; <b>and</b>
(d)	Original copy of Bid Security. If in the form of a Surety Bond, submit also certification issued by the Insurance Commission; <u>Or</u> Original copy of Notarized Bid Securing Declaration; <b>and</b>
(e)	Conformity with the Technical Specifications, which may inclu production/delivery schedule, manpower requirements, and/or aft sales/parts, if applicable; <b>and</b>
(f)	Original duly signed Omnibus Sworn Statement (OSS); and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authorit to its officer to sign the OSS and do acts to represent the Bidder.
Financi	al Documents
(g)	The prospective bidder's computation of Net Financial Contracting Capacity (NFCC); <u>or</u> A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation.
	Class "B" Documents

	(h)	If applicable, a duly signed joint venture agreement (JVA) in case the joint venture is already in existence; <u>or</u> duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.
<u>Oti</u>	her do	ocumentary requirements under RA No. 9184 (as applicable)
	(i)	[For foreign bidders claiming by reason of their country's extension of reciprocal rights to Filipinos] Certification from the relevant government office of their country stating that Filipinos are allowed to participate in government procurement activities for the same item or product.
	(j)	Certification from the DTI if the Bidder claims preference as a Domestic

Bidder or Domestic Entity.

## FINANCIAL COMPONENT ENVELOPE

(a) Original of duly signed and accomplished Financial Bid Form; **and** 

(b) Original of duly signed and accomplished Price Schedule(s).



### **Annex A: Bid Securing Declaration Form**

[ shall be submitted with the Bid if bidder opts to provide this form of Bid Security]

REPUBLIC OF THE PHILIPPINES) CITY OF \_\_\_\_\_\_) S.S

#### BID SECURING DECLARATION

#### Project Identification No.: [Insert number]

To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- I/We understand that, according to your conditions, bids must be supported by a Bid Security, which may be in the form of a Bid Securing Declaration.
- 2. I/We shall furnish the required performance security within ten (10) calendar days in/ Case of receipt of Notice of Award (*pursuant to GPPB Circular No. 04-2020 and GPPB Resolution No. 16-2020*).
- 3. I/We accept that: (a) I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of two (2) years upon receipt of your Blacklisting Order; and, (b) I/we will pay the applicable fine provided under Section 6 of the Guidelines on the Use of Bid Securing Declaration, within fifteen (15) days from receipt of the written demand by the procuring entity for the commission of acts resulting to the enforcement of the bid securing declaration under Sections 23.1(b), 34.2, 40.1 and 69.1, except 69.1(f),of the IRR of RA No. 9184; without prejudice to other legal action the government may undertake.
- I/We understand that this Bid Securing Declaration shall cease to be valid on the following circumstances:
- Upon expiration of the bid validity period, or any extension thereof pursuant to your request;
- b. I am/we are declared ineligible or post-disqualified upon receipt of your notice to such effect, and (i) I/we failed to timely file a request for reconsideration or (ii) I/we filed a waiver to avail of said right; and
- c. I am/we are declared the bidder with the Lowest Calculated Responsive Bid, and I/we have furnished the performance security and signed the Contract.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this \_\_\_\_\_day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE] [Insert signatory's legal capacity] Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

### **REFERENCE: GPPB RESOLUTION NO. 16-2020 / GPPB CIRCULAR NO. 04-2020**

Download from: https://www.gppb.gov.ph/downloadables.php

			For G	Goods Offered	from Ab	oroad		
lame	of Bidder				Project I	D No	Page	of
1	2	2	4	5	6	7	8	9
1	2	3	4	2	0		0	9
Item	Description	Country of origin	Quantity	Unit price CIF port of entry (specify port) or CIP named place (specify border point or place of destination)	Total CIF or CIP price per item (col. 4 x 5)	Unit Price Delivered Duty Unpaid (DDU)	Unit price Delivered Duty Paid (DDP)	Total Price delivered DDP (col 4 x 8)
ignat	ure:							
uly a	uthorized t	o sign th	e Bid for	and behalf of:				

# Price Schedule for Goods Offered from Within the Philippines [shall be submitted with the Bid if bidder is offering goods from within the Philippines]

ame	e of Bidder				Proje	Pageof			
1	2	3	4	5	6	7	8	9	10
tem	Description	Country of origin	Quantity	Unit price EXW per item	Transportation and all other costs incidental to delivery, per item	Sales and other taxes payable if Contract Is awarded, per item	Cost of Incidental Services, if applicable, per item	Total Price, per unit (col 5+6+7+ 8)	Total Pr deliver Final Destinat (col 9) (col 4
ame	:								
egal	Capacity:								
igna	ture:								
uly a	authorized	to sign th	ne Bid for	r and b	ehalf of:				

GPPB Resolution No. 16-2020, dated 16 September 2020

Page 24 of 39

Contract Agreement Form for the Procurement of Goods (Revised) [Not required to be submitted with the Bid, but it shall be submitted within ten (10) days after receiving the Notice of Award]

#### CONTRACT AGREEMENT

THIS AGREEMENT made the \_\_\_\_\_ day of \_\_\_\_\_ 20\_\_\_ between [name of PROCURING ENTITY] of the Philippines (hereinafter called "the Entity") of the one part and [name of Supplier] of [city and country of Supplier] (hereinafter called "the Supplier") of the other part;

WHEREAS, the Entity invited Bids for certain goods and ancillary services, particularly [brief description of goods and services] and has accepted a Bid by the Supplier for the supply of those goods and services in the sum of [contract price in words and figures in specified currency] (hereinafter called "the Contract Price").

NOW THIS AGREEMENT WITNESSETH AS FOLLOWS:

- In this Agreement words and expressions shall have the same meanings as are respectively assigned to them in the Conditions of Contract referred to.
- The following documents as required by the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184 shall be deemed to form and be read and construed as integral part of this Agreement, viz.:
  - Philippine Bidding Documents (PBDs);
    - i. Schedule of Requirements;
    - ii. Technical Specifications;
    - iii. General and Special Conditions of Contract; and
    - iv. Supplemental or Bid Bulletins, if any
  - Winning bidder's bid, including the Eligibility requirements, Technical and Financial Proposals, and all other documents or statements submitted;

Bid form, including all the documents/statements contained in the Bidder's bidding envelopes, as annexes, and all other documents submitted (e.g., Bidder's response to request for clarifications on the bid), including corrections to the bid, if any, resulting from the Procuring Entity's bid evaluation;

- iii. Performance Security;
- iv. Notice of Award of Contract; and the Bidder's conforme thereto; and
- v. Other contract documents that may be required by existing laws and/or the Procuring Entity concerned in the PBDs. <u>Winning bidder agrees that</u> <u>additional contract documents or information prescribed by the GPPB</u> <u>that are subsequently required for submission after the contract</u> <u>execution, such as the Notice to Proceed, Variation Orders, and</u> Warranty Security, shall likewise form part of the Contract.
- In consideration for the sum of [total contract price in words and figures] or such other sums as may be ascertained, [Named of the bidder] agrees to [state the object of the contract] in accordance with his/her/its Bid.

GPPB Resolution No. 16-2020, dated 16 September 2020

Page 26 of 39

4. The [Name of the procuring entity] agrees to pay the above-mentioned sum in accordance with the terms of the Bidding.

IN WITNESS whereof the parties hereto have caused this Agreement to be executed in accordance with the laws of the Republic of the Philippines on the day and year first above written.

[Insert Name and Signature]

[Insert Name and Signature]

[Insert Signatory's Legal Capacity] [Insert Signatory's Legal Capacity]

for:

for: [Insert Name of Supplier]

[Insert Procuring Entity]

Acknowledgment [Format shall be based on the latest Rules on Notarial Practice]

GPPB Resolution No. 16-2020, dated 16 September 2020

Page 27 of 39

### Omnibus Sworn Statement (Revised)

[shall be submitted with the Bid]

REPUBLIC OF THE PHILIPPINES ) CITY/MUNICIPALITY OF \_\_\_\_\_ ) S.S.

#### AFFIDAVIT

I, [Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:

1. [Select one, delete the other:]

[If a sole proprietorship:] I am the sole proprietor or authorized representative of [Name of Bidder] with office address at [address of Bidder];

[If a partnership, corporation, cooperative, or joint venture:] I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];

2. [Select one, delete the other:]

[If a sole proprietorship:] As the owner and sole proprietor, or authorized representative of [Name of Bidder], I have full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached duly notarized Special Power of Attorney;

[If a partnership, corporation, cooperative, or joint venture:] I am granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate, Board/Partnership Resolution, or Special Power of Attorney, whichever is applicable;)];

- [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, <u>by itself or by relation, membership, association, affiliation, or controlling interest with another blacklisted person or entity as defined and provided for in the Uniform Guidelines on Blacklisting;
  </u>
- Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- [Name of Bidder] is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;
- 6. [Select one, delete the rest:]

[If a sole proprietorship:] The owner or sole proprietor is not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical

GPPB Resolution No. 16-2020, dated 16 September 2020

Page 30 of 39

Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a partnership or cooperative:] None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a corporation or joint venture:] None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

- 7. [Name of Bidder] complies with existing labor laws and standards; and
- [Name of Bidder] is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
  - a. Carefully examining all of the Bidding Documents;
  - b. Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract;
  - Making an estimate of the facilities available and needed for the contract to be bid, if any; and
  - Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project].
- [Name of Bidder] did not give or pay directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity.
- 10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

IN WITNESS WHEREOF, I have hereunto set my hand this \_\_\_\_ day of \_\_\_\_, 20\_\_\_ at \_\_\_\_, Philippines.

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE] [Insert signatory's legal capacity] Affiant

[Jurat] [Format shall be based on the latest Rules on Notarial Practice]

GPPB Resolution No. 16-2020, dated 16 September 2020

Page 31 of 39

### Performance Securing Declaration (Revised)

[if used as an alternative performance security but it is not required to be submitted with the Bid, as it shall be submitted within ten (10) days after receiving the Notice of Award]

REPUBLIC OF THE PHILIPPINES) CITY OF \_\_\_\_\_\_ ) S.S.

#### PERFORMANCE SECURING DECLARATION

Invitation to Bid: [Insert Reference Number indicated in the Bidding Documents] To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- I/We understand that, according to your conditions, to guarantee the faithful
  performance by the supplier/distributor/manufacturer/contractor/consultant of its
  obligations under the Contract, I/we shall submit a Performance Securing Declaration
  within a maximum period of ten (10) calendar days from the receipt of the Notice of
  Award prior to the signing of the Contract.
- I/We accept that: I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of one (1) year for the first offense, or two (2) years <u>for the second offense</u>, upon receipt of your Blacklisting Order if I/We have violated my/our obligations under the Contract;
- I/We understand that this Performance Securing Declaration shall cease to be valid upon:
  - a. issuance by the Procuring Entity of the Certificate of Final Acceptance, subject to the following conditions:
    - i. Procuring Entity has no claims filed against the contract awardee;
    - ii. It has no claims for labor and materials filed against the contractor; and
    - iii. Other terms of the contract; or
  - b. replacement by the winning bidder of the submitted PSD with a performance security in any of the prescribed forms under Section 39.2 of the 2016 revised IRR of RA No. 9184 as required by the end-user.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this \_\_\_\_\_ day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE] [Insert signatory's legal capacity] Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

GPPB Resolution No. 16-2020, dated 16 September 2020

Page 32 of 39

Business Name: Business Addres								_		
Name of		Owner's Name		Bidders Ro	ole	a.	Date Awarded	% of Accor	nplishment	Value of
Contract/ Project Cost	b.	Address Telephone Nos.	Nature of Work	Description	%	b. c.	Date Started Date of Completion	Planned	Actual	Outstanding Works Undelivered Portion
Government	_									
Private	_									
Filvate										
								Total Cost		
Submitted by:										
Submitted by:		·(Pri	nted Name	and Signature)			_			
Designation: Date:		: :					_			

Name of Contract/	a. Owner's Name	Nature of	Bidders Rol	e	a. Date Awarded		
Project Cost	b. Address c. Telephone Nos.	Work	20 CT-10 CT-		b. Date Started c. Date of Completion	Value of Works	
			2			-	
			3				
			5				
statement during Po Notice of Awa Copy of actua	g documents shall be ost-Qualification: rd OR Notice to Proceed i I contract OR its equivaler Completion OR End-user's	ssued by the En	d user OR its equiva		Total		
Submitted by:	:(Printed Na	ame and Signatu	re)				
oublinitiou by:							
Designation:	2						

